

## **ProSet® PB2500** Battery Tool for Blind Rivets



# High speed cordless power tool with great strength and endurance.

## EASY

Tool free, quick release nose housing and jaw guide removal

## LIGHT

Weight only 3.75 lbs, including battery

## STRONG


1,911 lbf Pulling Force

## **TIME SAVING**

Ensures continuous operation in production environments without 'tool overload'

#### **Rivet holding mechanism**

Rivets do not drop out – even when tool is set upside down



#### Integral mandrel collector

Large capacity collector stores up to 600 spent mandrels

#### Easy nose housing removal

18V/11-10N 2.044

Tool free, quick release nose housing and jaw guide removal and installation







## **ProSet® PB2500 Battery Tool for Blind Rivets**

Lightweight tool with excellent ergonomics, great strength and great added features. Ensures high productivity and improve your return on investment with very low installation cost.

- **Durable** brushless motor that requires minimal maintenance
- Long lasting battery capable of placing an average of 1,200 ø 3/16" standard blind rivets per charge
- **Time saving** continuous operation in production environments without "tool overload"
- Easy to use: Quick release nose housing and jaw guide; Rivet holding mechanism; Quick slide battery installation

## **Placing Capacity**

Rivet Type	Placing Capacity (mm)					
	2.0	<b>2.4</b> (3/32")	3.0	<b>3.2</b> (1/8")	<b>4.0</b> (5/32")	<b>4.8</b> (3/16")
Open End	$\bullet^{\dagger}$	•**		•	•	•
Closed End				•*	•*	•*
Avex <sup>®</sup> /Stavex <sup>®</sup>			٠	٠	٠	٠
Avinox <sup>®</sup> /Avibulb <sup>®</sup>				٠	٠	•*
HR/HT				•	٠	•*
Interlock®						•*
Klamp-Tite®						٠
Bulbex <sup>®</sup> /LS/TL				٠	٠	٠
Monobolt®						•†
Multi-grip				٠	٠	٠
Pull-Thru (PT)			$\bullet^{\dagger}$	•†		
Q Rivet				•	•	٠
T-Lok®						٠
T Rivet						•†
Avseal®					• <sup>†</sup>	

\* Non-Standard nosepiece required

\*\* Non-Standard nosepiece and jaws required

t Contact STANLEY Engineered Fastening, Applications Engineering for assistance



www.StanleyEngineeredFastening.com

© 2016 Stanley Black & Decker, Inc., Rev. 11.2016

STANLEY Engineered Fastening 4 Shelter Rock Lane Danbury, Connecticut 06810 **United States** Tel. 877 364 2781 Fax. 800 225 5614

STANLEY Engineered Fastening 1030 Lorimar Drive Mississauga, Ontario L5S 1R8 Canada Tel. 800 268 9947 Fax. 800 594 7661

**STANLEY Engineered Fastening** 

### **Dimensions**



2.0Ah battery with charge indicator

## **Specifications**

Dimensions: Battery:	LxH 320 mm x 240 mm (12.6" x 9.4") 18V Li-Ion 2.0Ah slim battery pack EBC183-NA, with charge indicator
Charger:	EBC101-NA, with progress lamp display,
	35 minute charge time
Piston stroke:	25 mm (0.984")
Pulling force:	8,500 N (1,911 lbf)
Noise level:	74 dB(A)
Capacity:	Standard rivets ø2.4-4.8 mm (3/32 " - 3/16 ")
Weight:	1.72 kg (3.75 lbs) including battery

## **Package Contents**

- 1 x PB2500 tool with nosepiece size ø4.8 mm (3/16")
- 1 x Battery 18V Lithium-Ion 2.0Ah
- 1 x Charger
- 1 x Bag with nosepiece and jaw pusher Ø3.2 mm (1/8")
- 1 x Bag with nosepiece and jaw pusher ø4.0 mm (5/32")
- 1 x Instruction Manual

Av. Antonio Dovali Jaime No 70 Torre B, Piso 9 La Fe, Santa Fe Mexico, D.F. 01210 Tel. +52 55 5326 7100 Fax. +52 55 5326 7141

Avdel®, Avex®, Stavex®, Avinox®, Avibulb®, Interlock®, Klamp-Tite®, Bulbex®, Monobolt®, T-Lok®, Avseal®, POP® and ProSet® are registered trademarks of Stanley Black & Decker, Inc. and its affiliates. Data shown is subject to change without prior notice as a result of continuous product development and improvement policy.