TRUCK / CV SPECIAL 2025









NEW!

176N-7 Assistent

Made in Germany

- Newly designed modern plastic cover with textures and large recessed, fully usable work surface
- Handle and swivel castors can be mounted either on the left or right
- Bevelled edges prevent damage
- Numerous fastening options for further accessories on both sides and rear screw-on points
- 2-stage locking system (central locking and mutual drawer locking)



NEW!

Tool set 163-614/16

HAZET

176N-7

811: **○** 0.5x3.0 − 1.2x6.5 mm 811: **○** PH 1, PH 2 **○** T10 − T30


Equipment

Made in Germany

176N-7/193 EAN-No. 4000896264810 Assistent[®] 176N-7

with 193 expert tools

- With new inserts: 163-613/152 / 163-614/16
- Mini reversible ratchet for bits 863MB
- SmartCase 2200SC-3
- New screwdriver series 811
- Universal pliers 760-26



Combination wrench set 163-30/25

© s6−24 mm s6x7−21x22 mm





Tool set 163-613/152 63 ¼ s 4 − 13 mm 129 ½ s 10 − 32 mm



Handle can be mounted on the left or right



Fully sealed work surface protects inside of trolley from leaking liquids



Incl. handle strips and bevelled edges









Configure your trolley the way you want it!

- Our perfect organisation system for your tool trolley
- All your tools are snugly embedded in high-quality 2-component soft foam inserts
- Endless combination options mean you can arrange yourtrolley according to your needs
- You can find more inserts at: www.hazet.de



EAN-No. 4000896+

264681

You can find suitable soft foam

You can find suitable soft foam inserts here \rightarrow

179NX

 $\mathcal{A}ssistent^{\circ}$

- Can be filled with 1/3, 1/3+, 2/3, 2/3+,

3/3, 3/3+ soft foam inserts • Dimensions (H x W x D): 1,020 x **786** x 518 mm

inserts here \rightarrow



made in deim	any		
HAZET No.	Number of drawers	EAN-No. 4000896+	
179NX-6	6	215560	
179NX-7	7	215577	
179NX-8	8	215584	



You can find suitable soft foam inserts here \rightarrow

179NXL Assistent[®]

- Can be filled with 1/3, 1/3+, 2/3, 2/3+, 3/3, 3/3+, 4/3+ soft foam inserts
- Dimensions (H x W x D): 1,020 x **959** x 518 mm

- Made III derinany					
HAZET No.	Number of drawers	EAN-No. 4000896+			
179NXL-6	6	215171			
179NXL-7	7	215164			
179NXL-8	8	215218			



You can find suitable soft foam inserts here \rightarrow

179NXXL Assistent[®]

- Can be filled with 1/3, 1/3+, 2/3, 2/3+, 3/3, 3/3+, 4/3+, 5/3+ soft foam inserts
- Dimensions (H x W x D): 1,020 x 1,133 x 518 mm

Made in Germany


made in denni						
HAZET No.	Number of drawers	EAN-No. 4000896+				
179NXXL-7	7	214624				
179NXXL-8	8	214778				




Tool assortments for soft foam inserts

Our commercial vehicle recommendations!






































Double precision in perfection!

- Developed and produced "Made in Germany"
- High permanent load for durability
- 90 teeth, 4° fine serration for confined spaces
- Locking function of the lever offers protection against unwanted switching
- A lot more performance with the same dimensions
- Strict production tolerances prevent dirt from getting in





































Discover our Smart Series

- Concept idea: Maximum number of tools stored in the smallest possible space for the best possible overview
- Functionally designed tool storage with pleasant feel
- Tool supplement "To Go": should always be taken along when there is something to be screwed quickly





850SR-7 EAN-No. 4000896249626

1/4" SmartRail with 7 slots, empty

• Dimensions: 245 x 37.4 x 29.2 mm









Made in Germany

900SR • 992T-SR 1/2" SmartRail with slots

for sockets

- Magnetic underside ensures grip on all ferrous surfaces, e.g. on tool trolleys, tool panels, machines, lifting platforms and in metal drawers
- Flexible plastic connector strip with 1/2" square slots
- Easy to clean material and pleasant surface feel
- Durable, robust twist lock for a tight fit and instant access
- Securely fixed when locked, turn socket left to remove
- Incl. robust metal lug for hanging, e.g. on a hook

Sma	SmartRail with empty slots Made in Germany					
No.	HAZET No.		Slots (empty)	LxW mm	EAN-No. 4000896+	
1	900SR-5	125 1/2	5	245 x 37.4	244508	
2	900SR-8	125 1/2	8	365 x 37.4	244515	





SmartRail v	with fitted	d slots
-------------	-------------	---------

No.	HAZET No.		Slots	Contents	LxW mm	EAN-No. 4000896+	
3	900SLG-SR/5	125 1/2	5	Socket, long s 13 · 17 · 19 · 22 · 24 mm	245 x 37,4	245277	
4	992T-SR/8	125 1/2	8	TORX®, short \$ T20 · T25 · T30 · T40 · T45 · T50 · T55 · T60	365 x 37,4	245376	



Grip pliers wrench series 762 and universal pliers series 760:

- Developed and produced by HAZET "Made in Germany"!
- Compact and at the same time highly resilient
- One-hand presetting possible
- Available in four lengths in 125, 150, 180 and 260 mm



762

Grip pliers wrench series

- Convenient thanks to quick adjustment with proven HAZET tip / step lever function
- Permanent laser-marked scaling for easy setting and reading
- High corrosion resistance due to chrome-plated, easy-to-clean pliers legs
- Pleasant to grip thanks to double dip coating lies well in the hand!
- Fine detent enables any wrench size in the clamping range



Made in Germany

	•								
HAZET No.	/ mm	Detent distance mm	Detent positions Number	Clamping range mm	EAN-No. 4000896+				
762-12	125	2,0	12	26	249800				
762-15	150	2,0	15	33	249640				
762-18	180	2,0	19	42	249787				
762-26	260	2.5	20	56	249664				





Nail and wire holder

Hexagon

Square



One-hand operation with



Flat material



Clamping range lasered

762

Protective jaws for 762-18, 762-26

• Contents: 3 pairs

Made in Germany

HAZET No.	Protective jaws for	EAN-No. 4000896+	
762-018/6	762-18	259861	
762-026/6	762-26	259885	







760

Universal pliers series

• Long service life due to extremely hard jaw serration

More force thanks to teeth offset against the direction of rotation!

- Precise detent distance with the aid of laser-cut serration
- Ergonomic sits comfortably in the hand thanks to double dip coating Convenient – thanks to quick adjustment with proven HAZET tip / step lever function
- Heavy-duty pliers legs made of case-hardened chrome vanadium steel






Production





Product video







Tube



Nail and wire holder function



Hexagon



Flat material



Square




One-hand operation with tip/step lever function



SYSTEM 5000-3CT Torque wrenches – our workshop classics!

- Large measuring range: 1 800 Nm
- 10 versions incl. 1/4", 3/8", 1/2", 3/4" reversible ratchet with square drive for commercial vehicle applications
- Accuracy: ±3 % of scale value (5107-3CT: ±4 %)
- Tested according to DIN EN ISO 6789-2:2017 with calibration certificate and serial number
- HAZET's own service centre for best aftersales service
- Developed and produced by HAZET "Made in Germany"
















TwinTurbo

- The strongest HAZET impact wrench series ever!
- Twin Effect More power in less time!
- Two air inlets and four air outlets
- 8-blade air motor with 25% higher impact performance ensures maximum torque










9014PS-1 · 9014P-1

1" Impact wrench

- Loosening torque (max.): 3,400 Nm
- Output designed with hole for pinning, as well as a nut-driver holder ring
- One-hand reversing switch
- Reduced vibrations
- Coupler plug (incl.): 10 nominal size
- Forward/reverse: three stage
- Tightening torque (max.): 2,712 Nm
- Working pressure: 6.3 bar
- Rotation speed: 5,500 rpm
- Air requirement 283 I/min (4.7 I/sec)
- Sound pressure level (at working pressure): 103.5 dB(A) Lp A
- Air inlet: inside thread 1/2" (20.67 mm)





25 1″

No.	HAZET No.	Designation	EAN-No. 4000896+	
1	9014PS-1	1" Impact wrench · short 382 mm	222490	
2	9014P-1	1" Impact wrench · long spindle 587 mm	218332	

9033N-4 EAN-No. 4000896210183

Belt sander

- Continuous speed regulation via speed regulator on back of handle
- For narrow surfaces (belt width 10 mm)
- Including three abrasive belts 330 x 10 mm (grain size 80, 100, 120)
- · Locking device for quick belt changing
- Automatic belt adjustment
- Length (total): 291.4 mm
- Weight (net): 0.81 kg
- Coupler plug (incl.): 7.2 nominal size
- Length (total): 291.4 mm



HAZET No.	4	Designation	EAN-No. 4000896+	
9033N-4	1	Belt sander	210183	
9033-480/10	10	Abrasive belt set: Grain size 80	139101	
9033-4100/10	10	Abrasive belt set: Grain size 100	139118	
9033-4120/10	10	Abrasive belt set: Grain size 120	139125	

9035-5 EAN-No. 4000896132355

Needle scaler

- Adjustable needle cover
- Removes precise, small and large emerging patches of rust
- 19 needles (Ø 3 mm)
- 3,200 impacts/min
- Weight (net): 2.6 kg
- Air requirement: 170 I/min (2.8 I/sec)
- Total length: 321 mm
- Coupler plug (incl.): 7.2 nominal size



HAZET No.	4	Designation	EAN-No. 4000896+	
9035-5	1	Needle scaler	132355	
9035-050	19	Spare needles for needle scaler 9035-5, Ø 3 mm, length 181 mm	139385	

9035M-6 EAN-No. 4000896258109

Mini needle scaler

- Gentle cleaning of soiled/rusted parts
- especially cleaning of brake systems etc. • Extremely slim/short pin form and free needles allow you to reach difficult to access areas as well
- 13 thin stainless steel needles (Ø 1.3 mm)
- 3,000 impacts/min
- Length: 236 mm






Adjustable needle carriage with integrated needle guide



With air outlet adjustable by 360°



HAZET No.	4	Designation	EAN-No. 4000896+	
9035M-6	1	Mini needle scaler	258109	
9035M-050	13	Spare needles for mini needle scaler 9035 M-5, Ø 1.3 mm, length 81 mm	233205	

9041G-1 EAN-No. 4000896212385

Tyre inflator · calibrated

- Manometer measuring range: 0−12 bar, graduation: 0.1 bar
- Pressure (max.): 12 bar • Temperature range: -20 to 60 °C
- Scale values in bar
- · Hose with plug-in nipple
- Measuring tolerance: -15 °C to 25 °C, 0 to 4 bar: ±0.08 bar, from 4 to 12 bar: ±0.16 bar
- Hose length: 1,000 mm
- Recalibration possible





9041D-1 EAN-No. 4000896212378

Tyre inflator · digital

- Manometer measuring range: 0−12 bar, graduation: 0.01 bar
- Pressure (max.): 12 bar
- Temperature range: -20 to 50 °C
- Display toggles between bar/PSI/kg/cm²
- Hose with plug-in nipple
- Measuring tolerance: -15 °C to 25 °C: ±0.1 bar
- Hose length: 400 mm





9041-1 EAN-No. 4000896147076

Tvre inflator · standard

- Manometer measuring range: 0−12 bar, graduation: 0.1 bar
- Pressure (max.): 12 bar
- Temperature range: -10 to 40 °C
- Scale values in psi and bar
- Hose with plug-in nipple
- Measuring tolerance: -15 °C to 25 °C: ±0.3 bar
- Hose length: 400 mm

Top seller!

















9040-4/6 EAN-No. 4000896263660

2-way air blow gun cone set

- For blowing out pipes, boreholes, etc. to form a seal • Compressed air cleaning of clogged or dirty lines/hoses, e.g. fuel, air conditioning and AdBlue® lines, hydraulic lines as well as windscreen washer system and coolant
- Adaptable to 2-way air blow gun 9040-4 and 9040Lg-3/2 (long version)
- Loosening stuck ignition coil plugs (pneumatic inflation)

- ① Stainless steel extension 187 mm (9040-41)
- ② Air blow gun with long nozzle
- 3 Short nozzles (not available individually)
- Set of cone nozzles, 3-piece (9040-42/3):
- 4 Cone nozzle Ø 13 mm5 Cone nozzle Ø 35 mm
- ⑥ Cone nozzle Ø 25 mm



HAZET No.	4	No.	Article	EAN-No. 4000896+
9040-41	1	1	Stainless steel extension for 9040-4, Length 187 mm	254781
9040-4	1	23	2-way air blow gun including short and 112 mm long nozzle	176236
9040-42/3	3	456	Set of cone nozzles for 9040-4	254767

9040-43/5 EAN-NO. 4000896263646

Nozzle set

- Extension of the application ranges of the 2-way air blow gun 9040-4 and the long air blow gun 9040Lg-3/2
- Wide range of applications thanks to various nozzle designs
- Connection (outside thread): 1/8" PF 28

- ① Long rubber nozzle 63 mm (scratch protection) ② Short rubber nozzle 13 mm (scratch protection)
- 3 Plastic surface nozzle (surface cleaning)
- 4 Metal nozzle with spherical air outlet (non-blocking)
- (5) Metal nozzle with safety function (non-blocking)



① 9040LG-3/2 EAN-No. 4000896206339

Air blow gun

- Incl. ② 90° lateral nozzles and **③ Venturi nozzles**
- For cleaning areas with restricted access on vehicles, machinery and agricultural machinery
- Grip area with insulated lance to protect it from cold
- Pressure (max.): 12 bar
- Working pressure: 6.3 bar
- Length (total): 1,085 mm
- Air requirement: 450 I/min (7.5 I/sec) • Coupler plug (incl.): 7.2 nominal size
- Thread 1/8" PF 28





90° lateral nozzle enables cleaning of cooling fins



100% increase in air outlet quantity thanks to Venturi effect

No.	HAZET No.	4	Article	EAN-No. 4000896+	
1	9040LG-3/2	3	Extra long air blow gun	206339	
2	9040LG-3-02	1	Lateral nozzle 90°, length 32 mm	241521	
3	9040LG-3-01	1	Venturi nozzle, length 54 mm	241514	


1



9040T-1 EAN-No. 4000896252626

Turbo air blow gun

- Cleaning dirty surfaces
- Swirl nozzle generates a strong air pulse for cleaning even stubborn dirt
- Plastic housing protects against scratches • Air inlet: inside thread 1/4" (12.91 mm)
- Coupler plug (incl.): 7.2 nominal size
- Hose diameter (recommended): 10 mm
- Pressure (max.): 12 bar
- Sound pressure level (at working pressure): 91 dB(A) Lp A
- Sound power pressure (at working pressure): 102 dB(A) Lp W
- Air requirement: 80 I/min (at working pressure)
- Weight (net): 0.16 kg












9042N-1 EAN-No. 4000896176472

Grease gun, pneumatic

- Continuous pumping of grease
- · Gun-filling with grease cartridges, loose grease or via dispenser
- Filling capacity (approx.): 400 ml
- Air requirement: 230 I/min
- Nylon tube: 230 mm
- Metal tube: 172 mm • Weight (net): 2.0 kg
- Coupler plug (incl.): 7.2 nominal size
- 360° adjustable handle





9048P-2/3, EAN-No. 4000896234608

Wash-gun set

- Effective, powerful and solvent-free cleaning of e.g. cooling systems with graduated system cleaning nozzle
- Cleaning without the use of aggressive chemicals or solvents
- Swivel joint at the water connection, helps to avoid "hose spaghetti"
- Continuous independent regulation of water and compressed air supply
- Temperature range -10 to 40 °C
- Weight (net): 0.4 kg
- Coupler plug (incl.): 7.2 nominal size



Contents:

Jet washing nozzle ①




• Water connection variants: 1/2" (13 mm) nipple for water coupling (Gardena system

compatible) or 3/4" (20 mm) GHT hose thread



Offers tidiness in the workshop – cable not left lying around, thus reducing the risk of accidents!





Hose stop at any point

9040D-2.5, EAN-No. 4000896214631

Cable reel

- Including line circuit breaker • Only suitable for indoor use
- 230 V AC
- Cable: H07RN-F 3 x 2.5 mm²
- Cable length: 20 m • Connecting cable length: 1.5 m
- Automatic guidance winds the hose neatly
- Braked winding to prevent risk of accidents
- Weight (net): 9.2 kg



9040N

Hose reel

- · Suitable for compressed air or water
- Working pressure (max.): 20 bar
- Temperature range: -40 to 60 °C
- Hose length: 15 m
- Length of connection hose: 0.9 m
- Automatic guidance winds the hose neatly
- Braked winding to prevent risk of accidents





No.	HAZET No.	Outside thread mm	Hose inside Ø mm	Δ'Δ g	EAN-No. 4000896+	
1	9040N-10	3/8" (16.41 mm)	10	6.45	206445	
2	9040N-13	1/2" (20.96 mm)	13	9.50	214648	





1

9000-061 EAN-No. 4000896195299

Safety coupling $0 - 20 \, bar$

- For air connection nipple 7.2 mm
- Air inlet thread (internal thread): 16.41 mm 3/8"

Suitable for hose reel 9040N-10



9000-062 EAN-No. 4000896218936

Safety coupling $0 - 50 \, bar$

- For air connection nipple 10 mm
- Air inlet thread (internal thread): 20.95 mm 1/2'

Suitable for hose reel



9040N-13

90400S-10, EAN-No. 4000896252602

Open hose reel, 20 m

- Allows visual inspection of the hose
- Automatic hose reel offers tidiness in the workshop —
 Hose not left lying around, thus reducing the risk of accidents
 Open design against accumulation of dirt

- For compressed air • Inside diameter of the hose: 10 mm
- Hose length: 20 m
- Working pressure (max.): 12 bar • Spring return with ratchet locking holders
- Including sturdy swivel base
- Integrated roller inlet
- Hybrid polymer hose, black
- Connection hose (length): 1 m
- Air inlet: outside thread 3/8" (16.41 mm)
- Including German air connection nipple for air inlet 9000-015
- Can be used with HAZET safety coupling 9000-061
- Installation via metal bracket or swivel base (included)
- Including ARO 210 nipple
- Weight (net): 11.68 kg



You can find more couplings at: www.hazet.de





9040-7 · 9040S-10

Spiral hose

- High flexible polyurethane hose
- Connecting pieces with 360° swivel joints
- Temperature range: -20 to 60 °C Hose length: 7.62 m
- · Working pressure: 10 bar



For compact hose management!

HAZET No.	Hose inside Ø mm	Δ'Δ g	EAN-No. 4000896+
9040-7	6.35	0,63	153404
9040S-10	10	11,68	212361

Robust steel design with ball-bearing guiding rails!





Including 9000-015














500

400

92

1.250

550

229529


244607


4 2134-1250

5 2132-3

Riving axe

Pickaroon





TOTALLY INSPIRING!

Revolutionary new HAZET cordless tool SYSTEM compatible with all devices of the new 9500 SYSTEM

- Power to work independently
- Innovative battery technology
- Enhanced performance
- Variety of devices
- More applications
- Extremely compact machinery







18V Rechargeable battery system 9500 I 18 V

No.	HAZET No.	Article	Benefits of the product	EAN-No. 4000896+
1	9530-10	Cordless drill 18 V	Tightening torque, hard (max.): 65 Nm	266142
2	9512-600	1/2" Cordless impact wrench, compact 18 V*	Loosening torque (max.): 600 Nm	265053
3	9512-950	1/2" Cordless impact wrench	Loosening torque (max.): 950 Nm	265039
4	9513-2100	3/4" Cordless impact wrench 18 V*	Loosening torque (max.): 2,100 Nm	265015
5	9533-10	Cordless right-angle grinder 18 V*	Revolutions per minute: 10,000	265091
6	9534-10	Cordless reciprocating saw	Long stroke: 25 mm	265077
7)	9579-10	Cordless work light 18 V*	1,000 lm	265275
8	9590-10	Cordless heat gun 18 V*	2 temperature levels: 260 and 530 °C	265299
9	9544-10	Hybrid fan 18 V*/230 V	Hybrid function: Battery 18 V or power supply unit 230 V	264995
10)	9580-10	Professional hybrid cordless DAB radio with Bluetooth, 18 V* and 230 V	2 x 10 Watt	264971
11)	9543-10	Cordless dry vacuum cleaner 18 V*	Underpressure (max.): 12,000 Pa	264957

*Without battery and charger



Electric system 9500 | 230 V

HAZET No.	Article	Benefits of the product	EAN-No. 4000896+	
9633-10	Electric right-angle grinder 230 V (corded)	Revolutions per minute: 12,000	264919	
9643-10	Electric dry vacuum cleaner 230 V (corded)	Underpressure (max.): 23,000 Pa	264933	

Accessories for cordless dry vacuum cleaner 9543-10 and 9643-10 corded vacuum cleaner

No.	HAZET No.	Article	EAN-No. 4000896+	
1	9543-04/7	Cleaning set	270989	
2	9543-01/5	Fleece filter bag set	270965	
3	9543-02	Flat pleated filter	270941	
4	9543-03	Chassis	270927	





Battery with patented Thermatec $^{\circ}$ technology:

- Integrated cooling system to extend service life
- Electronic Management System (EMS) protects battery pack, extends service life and increases efficiency



Integrated LED light with persistence afterglow



Brushless motor with high efficiency and long service life
























Battery approx. Ba

Charger 9501-1018 with "traffic light display": Shows state of charge in colour (red-yellow-green) and remaining time until fully charged



Charge level indicator







NEW!



HAZET thermal camera – For the best possible view!

1992N-1 EAN-No. 4000896263523

Thermal camera

- · Automatic hot, cold and central point measurement
- Screen size: 2.4 inch LCD screen
- Display resolution: 320 x 240 pixels
- Battery life: up to 8 hours
- Storage medium: Micro SD card (included in delivery) up to 150,000 images
- Temperature range: -20 550 °C
- Protection rating: IP54
- SD card (4 GB) included
- Dimensions (H x W x D): 196 x 117 x 59 mm
- Weight: 290 g
- Charging via USB-C cable
- · Including hand strap






NEW

50°x 50°







Laser pointer for targeting



6 colour palettes for optimum diagnostics!

Enlarged field of view: 50° x 50°!





HAZET video borescope with HD camera – optimum detail!

• Bright and sharper image • better details • clearer image










4812-23/5AF EAN-No. 4000896249824

HD touch screen borescope set with swivelling probe 180°, Ø 3.9 mm





Probe tip 180° swivelling

Built-in microphone!

Marking details of photos on the touchscreen – Creating folders!

Split screen: Side-by-side display of recording and live image!







HD video borescope set with 360° swivelling probe Ø 3.9 mm



Removable Li-ion battery (1 x type 18650) without additional tools!

Fully articulating probe with Ø 3.9 mm!

Own smartphone as display,





HAZET L-Boxx 136:

- Basic unit 4812-23G
- HD probe 4812-23AF
- SD card 64 GB incl. adapte • Micro HDMI cable (A to D) 1.8 m
- USB-C cable (A to C) 1 m




	4812-23/5AF
Camera probe	Ø 3.9 mm probe with front camera can be swivelled up to 180° (articulation see ①)
Display	127 mm (5") large, sunlight-readable, reflection-reduced touch display
Zoom	3 x
Display resolution	800 x 480 pixels
Brightness setting	5 + 5 level boost
Energy source	Rechargeable Li-ion battery. Charging time: 3.5 h, operating time: 4 h
Image format (jpg)	1,920 x 1,080 pixels
Video format	MP4, 1,920 x 1,080 pixels (MOV format) with optional watermark, timestamp and audio
Data transfer	USB-C (access either to camera or as card reader)
IP protection rating (basic unit)	IP54
Connectivity	Camera can be used via HDMI on the display or USB-C on the PC
Weight	705 g
Dimensions (L x W x H)	162 x 128 x 46 mm

4-piece set in protective soft case with moulded insert:

- · Basic unit (fully integrated)
- HD probe
- 3 data cables (0.3 m) for USB-A to lightning USB-C and USB micro
- Charging cable USB-A to USB-C 1.0 m

4812-24/4AF	
9 mm probe with front camera can be swivelled up to 360° (2)	

380 g







Control over operating elements





NEW!

195N-2 EAN-No. 4000896252169

Mechanic's creeper

- Ergonomically shaped: cut out arm areas for optimal elbow room
- High capacity up to 150 kg
- Smooth-running swivel castors with rubber running surface, oil resistant and low-noise
- Six castors made of hard plastic (Ø 70 mm)
- Dimensions (L x W x H): 1,030 x 480 x 115 mm

Work comfortably under vehicles!











195N-3 EAN-No. 4000896256761

Creeper


- High capacity up to 150 kg (lying or sitting)
- 6 castors (Ø 63 mm)
- Combines creeper and seat
- Sturdy steel tube frame with 2.4 mm material thickness
- Dimensions (L x W x H): 1,198 x 440 x 135 mm (lying position)
- Seat height: 420 mm
- Seat surface: 300 x 310 mm

Sturdy steel tube frame with 2.4 mm material thickness!



195N-4 EAN-No. 4000896261949

Pneumatic chair



- \bullet Large, extra thick cushion \varnothing 350 mm
- Capacity: dynamic capacity up to 150 kg • Can be adjusted in height by hand: 430 – 550 mm
- Pneumatically adjustable in height
- Tilt-resistant


Particularly stable design thanks to square tubular frame!



9070-10 EAN-No. 4000896158157

Magnetic holder

• Loading capacity: 10 kg





NEW!



Commercial vehicle wheel hub grinder set

- Special grinder for optimal cleaning of the bearing surface of a wheel rim (wheel hubs) on trucks and transporters with stud bolts
- Hook and loop fastener for quick changing of grinding wheels
- Inc. 5 grinding wheels for moderate dirt and 6 for heavy dirt
- With hexagon insert for firm hold on the device • Octagonal profile for safe and firm fixation
- Inside Ø (max.): 23 mm
- Grinding wheels Ø: 56 mm









For stud bolts! No chip removal!

Made in Germany

www.hazet.de 17



- For brake fluid, battery fluid and non-acidic liquids
- Material: HDPE • Colour: white/transparent

Errors excepted.



No.	HAZET No.	Filling capacity	EAN-No. 4000896+
1	198-5	2	174478
2	198-6	5	174522
3	198-8	5	174508












New features for our power adapter! • For all sockets with outside hexagon s 24 mm • 2-in-1: One socket for two applications (1/2" · 3/4")










All items on this page are also available in a 40-piece set 163-612/40 in a tool trolley soft foam insert!























163-612/40 EAN-No. 4000896264704

1/2" • 3/4", 24 mm Impact socket set

- Screw connections on commercial vehicles, passenger cars and vans with TORX® profile, e.g. on the chassis, brakes, wheel screw connections
- Operation with various drive tools possible:
- 1/2" ratchet or impact wrench
- s 24 mm socket and box-end wrench.
- open-end wrench or ratcheting combination wrench
- Adapter 1003S-1 enables drive in 3/4",
 e.g. with HAZET 3/4" impact wrench 9013TT
- For HAZET Assistent with a drawer depth of 398 mm:
 173 ⋅ 179 ⋅ 179N ⋅ 179NX ⋅ 179NW ⋅ 179NW ⋅ 179BIG-1 ⋅
 179XL ⋅ 179XXL ⋅ 179XXL ⋅ 179XXXL ⋅
 179TXXL ⋅ 180

Contents:

O985S-14, -14Lg, -17, -17Lg, -19, -19Lg, -22, -24
900SZ6-18, -19, -21, -22, -24, -27, -30, -32, -36 **O** 995S6-T40, -T40Lg, -T45, -T45Lg, -T50, -T50Lg

O 903SLg6-17 · 6-19 · 6-21

O 900SLg6-24





You can find more tool trolley soft foam inserts in our soft foam configurator or on page 2!







990S-12/2 EAN-NO. 4000896264667

1/2", 24 mm outside hexagon impact screwdriver socket set,

internal serration XZN

- Operation with various drive tools possible:
- 1/2" ratchet or impact wrench
- -s 24 mm socket and box-end wrench or open-end wrench
- Adapter 1003S-1 enables drive in 3/4", e.g. with HAZET 3/4" impact wrench 9013TT

Design

short

long

• Screw connections on commercial vehicles, passenger cars and vans with XZN profile, e.g. on the chassis

2-piece set:

No.

1

2

- 1x 990S-12 (short, 43 mm)
- 1x 990S-12Lg (long, 75 mm)

HAZET No.

990S-12

990S-12Lg



5

39,7

43

75



d mm

24

24











O • 6

995S6/6 EAN-No. 4000896264780

1/2", 24 mm Impact socket set, inside TORX®

0

M12

M12

• Screw connections on commercial vehicles, passenger cars and vans with TORX® profile, e.g. on the chassis or brakes

Operation with various drive tools possible:

1/2" ratchet or impact wrench

- s 24 mm socket and box-end wrench or open-end wrench - Adapter 1003S-1 enables drive in 3/4",

e.g. with HAZET 3/4" impact wrench 9013TT • 995S6-T50Lg operation of the screw connection

on the steering knuckle when changing the brake discs or wheel bearings on **FORD** Transit model year 2006 \rightarrow

• Wrench sizes: T40, T45, T50

6-piece set:

- 3 short sockets (43 mm): 995S6-T40, 995S6-T45, 995S6-T50
- 3 long sockets (75 mm): 995S6-T40Lg 995S6-T45Lg, 995S6-T50Lg





NEW!

Made in Germany

NEW!

903SLg6/3 EAN-No. 4000896264643

1/2", 24 mm Outside hexagon traction profile, impact socket set

• Operation with various drive tools possible:

- 1/2" ratchet or impact wrench

-s 24 mm socket and box-end wrench or open-end wrench

- Adapter 1003S-1 enables drive in 3/4", e.g. with HAZET 3/4" impact wrench 9013TT

• Double protection: Easy-to-rotate external plastic sleeve (replaceable) to protect the rims when screwing wheel bolts. Plus: Internal plastic insert to protect the surface of wheel bolts

3-piece set:


- 903SLg6-17
- 903SLg6-19
- 903SLg6-21













HINT:

You can find our

suitable impact

and 9012PTT

Made in Germany

on page 9!

wrenches 9012ATT



900SK/10 EAN-No. 4000896246434

1/2" Impact socket set


- Particularly suitable together with short 1/2" impact wrenches e.g. HAZET 9012ATT, HAZET 9012PTT
- With borehole for locking pin or safety spring and groove for O-ring
- Surface: phosphatized, oiled
- DIN 3129, ISO 2725-2
- For impact operation • Length (total): 29 mm
- s 13, 14, 15, 16, 17, 18, 19, 21, 22, 24 mm
- In HAZET Safety-Insert-System (SIS)
 2-component soft foam insert 1/9 (W 172 x H 114 mm)

Extra short design!












125 1/2 🔞 🗖 10



In 1/9 soft foam insert





20 3/4″ 25 **1**″



1









1000SLG · 1100SLG

20 3/4" 25 **1**" 3/4" · 1" Impact socket (6-point)

- With borehole for locking pin or safety spring and groove for O-ring
- Surface: phosphatized, oiled
- DIN 3129, ISO 2725-2




3/4"



Length: 100 mm Made in Germany

HAZET No.	d ₁ mm	d ₂	<i>†</i>	EAN-No. 4000896+	
1000SLG-24	39.5	44	17	001392	
1000SLG-27	43.5	44	19	001408	
1000SLG-30	47.5	44	21	001422	
1000SLG-32	50.0	44	21	001439	
1000SLG-33	51.5	44	21	001446	
1000SLG-36	55.0	44	23	001460	





Length: 110 mm

wade in Gei	many			1
HAZET No.	d ₁ mm	d ₂ mm	<i>†</i>	EAN-No. 4000896+
1100SLG-24	41.5	54	17	002405
1100SLG-27	45.0	54	19	002412
1100SLG-30	49.0	54	21	002429
1100SLG-32	51.5	54	21	002436
1100SLG-33	52.5	54	21	002443
1100SLG-36	56.5	54	23	002467
1100SLG-38	59.0	54	24	002474
1100SLG-41	63.0	54	26	002481
1100SLG-46	69.5	54	28	002498



1004S · 1104S

3/4" • 1" Impact socket (6-point)

• DIN 3129, ISO 2725-1

- Especially long 6-point socket design e.g. for deep wheel nuts and bolts on commercial vehicles
- For impact operation
- Surface: phosphatised





1004S-33

- E.g. for deeply located wheel nuts and bolts on commercial vehicles
- With borehole for locking pin or safety spring and groove for O-ring




1104S-32

- For impact operation
- With bolt for locking pin retaining
- Surface: phosphatised



Made in Germany

No.	HAZET No.		[mm	d₁ mm	d ₂	† mm	EAN-No. 4000896+	
1	1004S-32	20 3⁄4″	400	48.0	44.0	32.0	055784	
2	10048-33	20 3⁄4″	400	48.0	44.0	32.0	055791	
3	1104S-32	25 1 ″	270	48.5	54.0	30.5	002665	





2166-4 EAN-No. 4000896161072

Commercial vehicle double-handled pry bar

- Shock-resistant, ergonomic plastic handle allows two-hand operation
- Hexagon blade passes through the handle
- Solid impact head for high loads











	0 ling pui adapte		
3 3 8 Ma	(4) (9) (de in German		(B) (T) (B) (B)
No.	HAZET No.	Components	EAN-No. 4000896+
1	4800-1	Cooling pump to 2.5 bar	022243
2	4800-2	Intermediary piece, flexible hose	022274
3	4800-3	AMAZONE Pantera · CLAAS Jaguar, Lexion, Scorpion, Ares, Atles, Ceres · DAF 45 model year 05/1991 → 12/2000 · D00SAN wheel excavators S · Caterpillar excavators Dx · FENDT · KAESER Mobilair · LIEBHERR A308-316 · MASSEY FERGUSSON with container no. 180224M92 and 4296015M1 · MERCEDES-BENZ Vito · Viano · Solaris · NISSAN forklifts · PUTZMEISTER BSA 1409 · SCANIA Vabis · CASE Quadtruc, Magnum	022281
4	4800-4A	DEUTZ engines 3.6 PowerPack · BF6M1013FC · TCD2013L6 2V and 4V Genset 250kV · HATZ 4H50tic · IVECO Eco Daily with blue lock · CASE Puma, SBS, LBS, Optum, Maxxum, CVX · NEW HOLLAND TVT, T7, T7 Elite Pack, T6 · FENDT Vario model year 2000 → combine harvesters L-Series · CLAAS Arion, Axion	156504
5	4800-5A	COMPAIR Mobile compressor with VW expansion tank · FENDT Farmer 300 model year 1988 → · Type 500 · Type 700 · Vario model year 1988 → 2000 · LINDE forklifts · PUTZMEISTER BSA 14070 · BSA 2110 HP-D · RENAULT Midlium model year 01/2000 → 12/2013 · Volvo FE model year 05/2006 → · FL model year 03/2000 →	161843
6	4800-16	DEUTZ engines KHD1015 · D2008 · D2009 · TD2.9 L4 · TCD3.6 · BFM1013 · BFM2012 · TCD2013 2V · BFM1015 · TCD2015 V8 · V6 · M · TCD 12.0 and 16.0 · MERCEDES-BENZ Sprinter model year 1999 → Type 170 · 208 · 611	098507
7	4800-17	JOHN DEERE tractors of Series 5, 6, 7, 8 and 9 · Forage harvesters of Series 8000 and 9000 · Self-propelled sprayer R4040, R4050, R4140 and 4150 · Windrower W170 · Cotton picker CP690 · Excavator 160DLC · Crawler dozer 700J · WHEEL LOADERS WL53, WL56 · HITACHI excavator ZAXIS 6 · HAGIE STS 10, 12, 14 and 16	109661
8	4800-18	MERCEDES-BENZ Sprinter since 2006, Viano since 2003	128815
9	4800-20	IVECO Euro-Star · Euro-Tech · Euro-Truck · Daily with black lock · MAN F90 · F2000 · TGA model year 03/2000 → · TGL model year 04/2005 → · TGM model year 10/2005 → · TGS model year 10/2007 → 01.2012 · TGX model year 10/2007 → 01.2012 · MERCEDES-BENZ commercial vehicles Actros · Atego 1217 model year → 1999 · Eco 8401 · SK1728 Antos · Arocs · Atego model year 1998 → 2013 · Axor model year 09/2001 → 10/2004 · Econic · Zentros · CLAAS Xerion, Tucano	144242
10	4800-21A	Volvo commercial vehicles · Scraper tractor dumpers	162185
(11)	4800-23	ISUZU truck · MITSUBISHI commercial vehicle Fuso Canter · NISSAN forklifts · YALE GDP/GLP 16-30	144273
12	4800-25	MAN buses such as Lions Coach · Lions Star · Lions Comfort · Lions City · MERCEDES-BENZ Citaro model year 01/1998	203857
13)	4800-26	DAF CF and XF Euro 6 from 2013	214495
(14)	4800-27	MERCEDES-BENZ Atego from model year 2014	214501
15)	4800-28	MERCEDES-BENZ Actros EURO 6 with HEYCO expansion tank from model year 2014	214518
16)	4800-29	SCANIA 143, G-/P- and R series	222780



9098/24 EAN-No. 4000896258086

Injector sliding hammer, pneumatic

- For removing stuck diesel injectors
- 21 different adapters and a universal claw can be used to gently loosen stuck diesel injectors without much effort
- Depending on the injector version, the piezo element must be removed for this purpose
- This prevents damage to the cylinder head/cylinder head cover due to high forces from supports
- In plastic case

24-piece set:

- Pneumatic diesel injector puller





Our problem solver

forall kinds of municipal

vehicles and vans!





772 mn











Injector extractor

- For disassembly of tight common rail injectors without removing the cylinder head
- For the simple removal of injectors together with sliding hammer, e.g. HAZET 1788T-1, on **MAN** engines D08, D20, D26 and D28
- Especially suited to the very limited space in the cylinder head
- Due to the tool's special claw, the injector may be gripped with caution, damagefree removal with the aid of the impact extractor
- Injector claw with inside thread M10 x 1.5 mm for insertion of the sliding hammer 1788T-1



To be used in combination with 1788T-1!

1788T-1 EAN-No. 4000896134304

Sliding hammer

- With coupler thread M 10 (sliding weight 200 g)
- Together with injector extractor 4797-5
- Coupler thread M10
- Incl. union nut









Exhaust probe sockets


- Robust design for fixed exhaust gas probes!
- Removal and installation of the lambda probe, particle sensor, NOX sensor and exhaust gas temperature sensor
- Double square 1/2" drive
- Torque-controlled tightening possible
- For manual operation
- Dimensions (L x H): 66 x 39 mm
- Slot width: 8 mm





Special tap for exhaust gas temperature sensors / probes

- Professional repair, cleaning or repairing of the mounting threads of the exhaust gas temperature sensors / probes
- Guide bolt prevents jamming of the thread repair tool, thereby enabling exact repair or cleaning of the sooty or damaged threads
- Time saving: replacement of the exhaust system is no longer necessary in most cases
- High-quality TiAIN coating for longer service life
- Suitable for application on stainless steel components
- **Drive:** s **13 mm**



4683 Thread repair tool for exhaust gas temperature sensors/probes Made in Germany EAN-No. **Thread** Length HAZET No. Use 4000896+ 1 4683-12 For exhaust gas temperature sensors on: IVECO M12 x 1.25 253555 For exhaust gas temperature sensors on: MERCEDES-BENZ Truck · AUDI · PORSCHE · SEAT · ŠKODA · VW · FIAT · ALFA ROMEO · LANCIA · OPEL 2 4683-14 M14 x 1.5 253579 For exhaust gas temperature sensors on: **MERCEDES-BENZ** Trucks, Bus & **DAF** commercial vehicles Actros (930, 932, 933, 934, 938) · Axor (375, 940, 942, 943, 944, 950, 952, 953, 954, 958) · Atego (375, 950, 952, 953, 954, 958) · MB Bus O 500 BM382 · **DAF** CF 65 · **DAF** CF 75 · **DAF** CF 85 · **DAF** CF 105 3 4683-16 M16 x 1.5 253593 4 For NOX sensors on: DAF · MERCEDES-BENZ Trucks · IVECO · MAN · SCANIA · RENAULT Trucks · Volvo Trucks 4683-20 M20 x 1.5 50 253630 For particle sensors on: MERCEDES-BENZ · MAN (5) 4683-22 M22 x 1.5 253654






4937-92 EAN-No. 4000896201952

3/4" Commercial vehicle pin wrench for front axle MAN

- Pin wrench for **MAN** trucks: E 2000 (ÖAF), F 2000, M 2000 L, M 2000 M MAN TGA, TGM, TGS, TGX
- MAN buses: Lions City, Lions Classic, Lions Coach, Lions Regio, Lions Star as well as older constructions (models), chassis
- NEOPLAN Cityliner, Starliner, Tourliner, Trendliner
- TEMSA Diamond, VISEON high-decker
- Diameter: 114 mm
- Length (total): 84 mm







20 3/4" 46

25 1″ 60 2

4937-62 EAN-No. 4000896199020


3/4" Commercial vehicle pin wrench for rear axle MERCEDES-BENZ

- Pin wrench for rear axle nuts
- MERCEDES-BENZ Actros, Atego (heavy design): LN2, SK rear axle
- · With outside guide collar
- Inside Ø: 62.8/70 mm
- 6 inside pins, pin width: 7.5 mm
- Length (total): 85 mm









20 3/4"

Made in Germany

20 3/4" 4


4937-111/2 EAN-No. 4000896201945

1" Commercial vehicle pin wrench set for rear axle MAN

- For **MAN** TGX, TGA, TGS e.g. rear axle: HY 1350
- 4-point drive: 1" (25 mm) and outside 6-point: s 60 mm • 6 pins, width: 11 mm
- Inside Ø: 134.5 mm • Inside Ø (pin-pin): 118 mm
- Outside Ø: 148.5 mm
- Length (total): 121 mm









4937-101/4 EAN-No. 4000896199266

3/4" Commercial vehicle pin wrench set for rear axle MERCEDES-BENZ

- For dismantling / assembly work on the rear axle as well as repair and maintenance work on the wheel hub, wheel bearing or brake disc
- MERCEDES-BENZ hub-reduction axle, such as trailing axle NR7/4
- MERCEDES-BENZ hub-reduction rear axles (Euro-axles) 10 t and 13 t,
- MERCEDES-BENZ hub-reduction axle 7 t AL7/1
- Inside Ø: 101.5 mm
- Length including guide tube (total): 140 mm
- 12 pins, width of pins: 11.4 mm
- With 3 replaceable guide tubes
- Outside Ø: 50, 51, 53 mm Length (total): 85 mm

Slotted nut



3/4"







لندو وليومننا

Made in Germany

20 3/4" 3



Commercial vehicle axle nut socket • Solid design: high (shape) stability even

- with very high loosening or tightening torques
- Surface: burnished







20 3/4" 36

Mad	de in	Gei	many	

No.	HAZET No.	Drive	Output s mm	Application	EAN-No. 4000896+	
1	4937-85	● s 36	85	SAF trailer axles	204267	
2	4937-90	● s 36	90	IVECO Daily 6.5 t; 7.0 t	199280	
3	4937-95	20 3/4"	95	IVECO Stralis and Eurofire, MERCEDES-BENZ Discos Trailer, BPW Eco plus	199457	

4937-103/3 EAN-No. 4000896199259

3/4" Commercial vehicle pin wrench set for rear axle MAN and MERCEDES-BENZ

- For repair and maintenance work on the wheel hub, wheel bearing or brake disc • For MAN and MERCEDES-BENZ 10 t and 13 t AP Hypoid and tag axle N7/4, bus 0305G, 0405G
- MAN hub-reduction rear axle F series H7, HD7
- Hypoid rear axle F series HY-1175, HDY-1175 Inside Ø: 103 mm
- Length including guide tube (total): 140 mm
- 6 pins, width of pins: 11.5 mm
- With 2 replaceable guide tubes
- Outside Ø: 51.5 mm, 66.5 mm • Length (total): 135 mm

















4937-105/2 EAN-No. 4000896201938

1" Commercial vehicle axle nut socket set DAF, RENAULT, Volvo


- Hexagon output: s 105 mm
- Drive: 1" (25 mm) and outside 6-point s 60 mm
- Screw-in guide tube allows for flexible application
- **DAF** with guide tube
- RENAULT, Volvo without guide tube
- · With outside guide collar













25 1″ 60 2



4937-87/3 EAN-No. 4000896199235


3/4" Commercial vehicle pin wrench set for MAN, **MERCEDES-BENZ**

- For repair and maintenance work on the wheel hub, wheel bearing or brake disc
- E.g. for MAN TGM 13T/15T exclusively 4x4 models Atego rear axle HL2, 814 Vitaro
- Pin wrench for rear axle, inside Ø: 87 mm
- Length (total): 65 mm
- 6 pins, width of pins: 10 mm
- With 2 replaceable guide tubes • Outside Ø: 49 mm, 57 mm
- Length including guide tube (total): 140 mm










20 3/4" 3

Made in Germanv

4937-80 EAN-No. 4000896199006

3/4" Commercial vehicle axle nut socket, **8-point,** *s* **80 mm**

- For dismantling/assembling the front axle nut with 8-point in front of the brake disc
- **SCANIA** series R, series 4, series 124–144 I etc. • Suitable for impact wrenches, e.g. HAZET 9013M
- Precise fit
- Parallel surfaces for perfect force fit on axle nuts
- Solid design: high (shape) stability even with very high loosening or tightening torques



20 3⁄4″







Made in Germany

4937

Commercial vehicle mounting sleeves

- Mounting sleeve to protect the thread on the axle during bearing disassembly and assembly • Only lift the 40 kg bearing unit (bearing + brake disc + wheel hub) onto the mounting sleeve
- once, then push up to the bearing seat • Drive via lateral rod or without additional tools is possible (ribbed handle surface)





— Ма	de in German	у				
No.	HAZET No.	Use	Thread mm	Outside Ø: mm	EAN-No. 4000896+	
1	4937-100	MAN TGX, TGA, TGS e.g. for MAN HY 1350 axle (13 t)	M 100 x 1.5	105	201983	
2	4937-7582	MAN TGL, TGM, L-Series, HL 2	M 75 x 1.5	82	201969	
3	4937-7578	MERCEDES-BENZ Atego, Atego 2, Tourino	M 75 x 1.5	78	201990	

125 1/2 3

4937



3/4" • 1" Commercial vehicle hub cap socket, Ø 110 mm and 120 mm for flat oval **BPW** hub cap

For **BPW** Eco and Eco Plus axles
 Perfect fit for **BPW** contour
Ø 110 mm, or Ø 120 mm



No.	HAZET No.		Ø mm	EAN-No. 4000896+
1	4937-120	20 3/4"	120	210459
2	4937-110	25 1 ″	110	199273

4937

1/2" Commercial vehicle centring sleeve set

- \bullet For fast assembly of centred truck drop centre rim wheels for rim hole \varnothing 26 mm
- No damage to the thread as well as exact centring
- of the rims thanks to conically cranked sleeves • Length (total): 115 mm



Made in Ge	ermany
HAZET	

HAZET No.	For rim hole ∅ 26 mm	EAN-No. 4000896+	
4937-26/3	M22 x 1.5 e.g.: DAF, FORD, MAN, MERCEDES-BENZ, RENAULT, Volvo	199013	
4937-27/3	7/8"-11G e.g. SCANIA	202010	







197-4 EAN-No. 4000896214235

Commercial vehicle axle oil collecting pan 3 l

- Safe collection of the oil dripping from the axle when disassembling or repairing the floating axles on trucks and agricultural machinery
- Chemical-resistant, unbreakable plastic
- with smooth, abrasion-proof surface • Dimensions (L x W x H): 310 x 240 x 160 mm



Made in Germany



Secure retention and movement of heavy components

- Suitable for all brake callipers and wheel hubs
- Brake calliper removal and installation with just one tool
- All brake service work can be carried out without straining your back
- Compatible with all brake callipers that have European type approval





4972-2 EAN-No. 4000896215393

Swivel bearing

- For disassembly and assembly of brake callipers in trucks, buses, trailers and trailer axles that are installed in a diagonal "clockwise position between 8 o'clock and 5 o' clock"
- Connect swivel bearing to brake calliper holder and position with e.g. jacking carriage below brake calliper. This enables easy insertion of the screws even in awkward positions
- Together with brake calliper holder HAZET 4972-1



4972-1/3 EAN-No. 4000896215799

Commercial vehicle lifting aids


- · Allows you to work safely, without straining your back, in tight spaces in the wheel arch on trucks, buses, trailers and trailer axles
- Significantly easier work when assembling
- and disassembling brake callipers and wheel hubs thanks to lifting aid
- No strain on the back
- Second person not required
- Makes screw tightening easier
- Secure hold for heavy components
- Takes the various installation situations of the brake calliper into consideration
- Secure movement with suspended components
- One-hand operation possible via spindle

Contents:

- Lifting aid
- · Brake calliper holder
- · Wheel hub holder

Accessories

Made in Germany							
No.	HAZET Designation		Function	EAN-No. 4000896+			
1	4972-1 Commercial vehicle brake calliper holder		Use with lifting aid 4972-3 or 4972-1/3	215423			
2	4972-4	Wheel hub holder	Use with lifting aid 4972-1/3	216031			







Brake calliper TORX® socket

- Operation of the brake calliper screw connection on MAN commercial vehicles
- Application: Brake calliper screws E20
- Drive: 22 mm outside hexagon
- Operation e.g. with HAZET socket box-end wrench 6630D-22 together with tool holder 6397 (loosening) or torque wrench 6293-1CT or 6295-1CT (tightening)



No.	HAZET No.	For e.g.	[mm	S mm	d ₁	d ₂	<i>†</i>	mm	EAN-No. 4000896+	
1	2871-E18	MAN TGM and TGL	39.5	E18	39.5	23.4	16.70	13.5	176175	
2	2871-E20	MAN TGM ⋅ TGA	39.5	E20	39.5	25.7	18.49	15.9	148790	
3	2871-E24	MAN TGA · TGS · TGX	39.5	E24	39.5	35.0	22.16	19.7	148783	



To be used by one person

Prevention of injuries

4969-612 EAN-No. 4000896204281

• Time saving and therefore also cost saving



Compressed air quick-connector releasing tool

• For operation with open-end s 13 mm (HAZET 600 N-13), no further tools necessary

• For plug connectors DIN 74324 6 x 1.0 · 8 x 1.0 · 10 x 1.0 · 12 x 1.5 · 12 x 2.0 mm

• Easy loosening of quick-connectors with Ø 6, 8, 10, 12 mm

• Enables separation of contaminated tubes and plug connectors





13

s 13 mm






20 3/4"










2872-E



• Laser-engraved formula for rapid conversion of the tightening torque specified by the manufacturer • Especially suitable for all repairs on the go, where no working pit is available • 2 impact areas enable the force to be applied using a hammer Highly stable and extremely resilient 3/4" 2 Made in Germany EAN-No. For *b* HAZET No. **a** mm No. 4000896+ e.g. **MERCEDES-BENZ** commercial vehicles 1 4937-19 215 120 12 30 215645 cardan shaft screw connections MAN commercial vehicles 2 120 215638 4937-21 215 12 30 cardan shaft screw connections

3/4" Box-end wrench · 12-point · with 2 striking faces

The 12-point profile allows application even in areas with hard-to-reach screw connections
 Application: Operation of usually very tight cardan shaft screw connection, even when the space available is limited





751LHS/5-1 EAN-No. 4000896**269440**

Drift punch set with hand guard, long

- Special safety impact head prevents material splintering and deformation
- Removing or countersinking splint pins, bolts or similar
- High-alloy tool steel, consistently hardened
- Gold-coloured immersion-lacquered
- With ergonomic two-component hard guard
- According to common standards (e.g. DIN)
- All metal parts are GS tested

Made in Germany

Length mm	Shaft Ø mm	Tip Ø mm						
751LHS-8 225		8						
240	14	10						
260	14	12						
275	18	14						
290	18	16						
	225 240 260 275	mm mm 225 14 240 14 260 14 275 18						





Universal ball joint puller


- Universal application e.g. for trucks, lightweight design
- Jaw opening a: 32 mm
- Clamping range sb: 85 mm



1790-3 EAN-No. 4000896145454

Ball joint puller

- For extracting the ball joint pivots of steering arms,
- steering tie rods, stabilisers Jaw opening a: 40 mm
- Clamping range sb: 85 mm







1779-55 EAN-No. 4000896136407


Ball joint puller

- For removing the ball joint pivots on steering tie rods, stabilizers, etc.
- Jaw opening: 55 mm
- Clamping depth: 80 mm



Quick-clamping puller • High strength and rigidity for safe work • Quick adjustment thanks to "one-nut" fixation per arm Two-arm puller st mm Forged arms • Inner and outer puller in one Quick and easy installation Solid all-steel bridge! st mm **Tonnes** sb mm Spindle EAN-No. HAZET No. 4000896+ 1750-34 345 260 M27 x 2 x 377 250042 20








Ball joint puller

- For the easy extraction of ball joint pivots
- and safe removal of ball joints
- Supported by hydraulic system






Made in Germany

HAZET No.	Q mm	sb mm	EAN-No. 4000896+	
1790-5	30 – 34	70	145461	
1790-6	36 – 40	85	145478	













HAZET - Tool expertise in the repair and maintenance of vans

Our recommendations for the light commercial vehicle, van and all kinds of van models:

We offer repair solutions for a wide range to ensure an adequate repair. Ensure better repair conditions, especially when repairing the chassis and surrounding components. Our high-quality tools are the perfect problem solver, saving time and money.

Our recommendation for wheel changes!



4960-200/3 EAN-No. 4000896143290

Wheel hub grinder

- Prevents incorrect wheel bolt tightening torque caused by corrosion
- Quick and easy removal of rust and dirt from contact surfaces of wheel hubs and brake discs with wheel bolt support
- For wheel hubs on passenger cars and transporters up to 200 mm e.g. **BMW** · **FIAT** Ducato · **MERCEDES-BENZ** Sprinter etc.
- Open-pored abrasive material and cup-formed grinding wheel reduce the formation of dust to a minimum
- No formation of sparks
- Wear-resistant: approx. 100 vehicles per wheel
- 10 mm 3-point pin, e.g. for the use in (air) drills • Max. revolutions/minute: 1,000
- Contents: 1 grinding pad, 2 grinding wheels
- Ø 200 mm



Better access for brake service and adequate bolt tightening!

NEW!



2784-2 EAN-No. 4000896263721

3/8" Brake calliper screwdriver socket, inside hexagon, s 6 mm

- Operation of the guide bolts s 6 mm at the rear break callipers of the MERCEDES-BENZ V-Class
- Screwdriver socket adapted to limited space conditions for easy use of operating toolsE
- For controlled screw tightening use a torque wrench with 3/8" (10 mm) drive, e.g. HAZET 6110-1CT or 5110-3CT (observe manufacturer's specifications)
- With fixed blade (s 6 mm) for inside hexagon screws
- For manual operation







Made in Germany

The releasing tool when it comes to suspension struts on new **Sprinter models!**

NEW!

125 1/2

2710-105 EAN-No. 4000896262946

1/2" Operating tool for fixing nut on spring strut **MERCEDES-BENZ Sprinter**

- Operation of the fixing nut for the spring strut on the **MERCEDES-BENZ** Sprinter Type 910 (with front-wheel drive) from model year 2018 \rightarrow and E-Sprinter from model year 2020 \rightarrow
- Optimally matched operating tool (space) conditions, loosening and tightening torques). Pay attention to the vehicle manufacturer's specifications
- Output: s 106 mm
- Outside diameter: 151 mm
- Height: 49 mm







Made in Germany

Impact wrench-compatible hand tools in 1/2", quick and easily adjustable to 3/4" if required, thanks to outside hexagon!

NEW!







163-612/40 EAN-No. 4000896264704

1/2" · 3/4", 24 mm Impact socket set

• Screw connections on commercial vehicles, passenger cars and vans with inside TORX® profile, e.g. on the chassis, brakes, wheel screw connections







You can find further information on the tools in the 163-612/40 18/19 on pages 18 and 19!





Made in Germany

4650-6 EAN-No. 4000896264629

Mini battery cell tester with QR code function

- Simple test of the starting capacity and condition of vehicle batteries and the starting and charging system
- Transfer of results to smartphone/tablet
- For 12 V systems in passenger cars, commercial vehicles and motorcycles as well as 12 V batteries
- 4 membrane keys
- Robust pole terminals with insulated handles
- Large, backlit LCD display
- Tests and detects defective cells in all types of starting batteries, including lead-acid batteries, AGM flat batteries, AGM spiral batteries, GEL batteries, start/stop batteries and rechargeable LI-ION batteries
- Device does not require its own battery and guarantees constant operational readiness
- Analysis of batteries in accordance with most battery standards, such as CGA, BCI, CA, MCA, DIN, IEC, EN, SAE, GB
- Reverse polarity protection to protect the device, vehicle and battery
- Large lithium battery working range,
 e.g. according to CCA standard 20 1,000 A

 Large lead-acid battery working range,
 e.g. to CCA standard 100 2,000 A
- Possibility of individualising the test results shared by QR code (number plate, repair workshop, tester, test date)







Starter test!

Alternator test!



NEW!

Lithium compatible	Storage temperature °C / °F	Operating temperature °C / °F	4 4	Dimensions (L x W x D) mm
✓	-20 – 70 / -4 – 158	0 - 50 / 32 - 122	200	80 x 80 x 22



2152-610 EAN-No. 4000896268542

Digital current clamp meter

- Measuring voltage, current and resistance
- With multimeter function
- AC/DC current measurement without disconnecting the cable
- Simple operation thanks to clear control panel and illuminated LCD display
- Small, handy, compact design for use in confined spaces
- Incl. continuity test, diode test, data hold and auto power-off function • Protective cover protects current clamp meter against dust and damage from being dropped
- Including CAT III test lead set
- Including 2 x 1.5 V AAA batteries Storage bag included
- ullet Pliers opening \varnothing 17 mm
- Measurement category: CAT III 300 V, CAT II 600 V
- Display: LCD with backlight • Diode test: Yes
- Data hold: Yes
- NCV: Yes
- Auto power-off function: Yes, after 15 minutes
- Capacitance measurement: Yes up to 20 mF
- Power supply: 2 x 1.5 V AAA
- Dimensions L x W x H: 33.50 x 60 x 175 mm
- Weight (without batteries): 150 g



3 testing devices in 1: current clamp meter, multimeter and (non-contact) voltage tester!












Detailed information





2152N/3 EAN-No. 4000896204151

Electronic set

- For troubleshooting on electronic components
- Measuring range 3 48 V
- Voltage display LED: 5, 12, 24, 48 V
- · Polarity display: LED for positive or negative, AC voltage with illuminated LED
- Additional crocodile clip and probe tip for attaching
- Cable length: 1,300 mm
- Probe tip, needle with sliding mechanism





1862N EAN-No. 4000896242627

Automatic wire stripper

- Automatic scanning system, no adjustment to the cable cross-section necessary
- Stripping of flexible cables (stranded wire) and solid conductors \varnothing 0.2 6.0 mm² or AWG 24 10
- Optimally positioned diagonal cutter up to 2.5 mm²
- Adjustable length stop: 6 − 15 mm
- · Replaceable blades
- Not for work on or near electrically live parts



4650-1 EAN-No. 4000896022014

Acid tester

- For checking the acid content of the battery fluid
- · With aerometer
- Significantly reduced risk of breakage compared to glass enclosures thanks to solid plastic housing
- Length: 280 mm



4650-3A EAN-No. 4000896249275

Special tool for battery plugs

- Special length allows universal application in areas with restricted access
- For screwing battery plugs in and out
- Profile is especially suitable for battery plugs
- Ergonomically shaped HAZET 2-component T-handle
- Surface: chrome-plated
- Screwdriver width: 14.5 mm
- Screwdriver height: 1.7 mm





A 4 125 1/2 125 1/2 1 125

810VDE · **◆**

810VDE • •

196V-10/5

196V-20/5

PH1 · PH2 · PH3

0,4 x 2,5 · 0,5 x 3 · 0,6 x 3,5 · 0,8 x 4 mm

150/39 EAN-No. 4000896239641

1/2" High-voltage tool set, with protective insulation

- Universally applicable on all trucks and buses, as well as agricultural and construction machinery with electric drives
- For operation of live components such as batteries, capacitors or distributors The use of two extensions enables simple and safe installation and removal of e.g. the battery thanks to the special insulation of the tools
- All the relevant tools for the operation of live fittings in one set
- · Highest level of safety through constant quality control of the tools • Delivery in new HAZET L-Boxx 136 – all tools ready to hand
- For e-trucks from e.g.: MERCEDES-BENZ, MAN, DAF, RENAULT, SCANIA and Volvo
- Suitable for use with electric urban buses such as e.g. MERCEDES-BENZ, MAN, VDL, IVECO, SOLARIS, Volvo, SCANIA, BYD, SILEO, LIKKER, COBUS, MELLOR, KARSAN, IRIZAR, EBUSCO, TEMSA, EURABUS, EASYMILE, NAVJA, LOCAL MOTORS, HEULIEZ















1860VDE-11

900KV • @ 129 1/2

s 13 · 14 · 15 · 16 ·

2156VDE-2




8816HPKV EAN-No. 4000896239184

₹ 1000 V 10 3/8 3/8" High-voltage reversible ratchet, with protective insulation

- 3/8" HiPer fine-tooth reversible ratchet with protective insulation
- 90 teeth, small operating angle of only 4°
- Sockets are securely locked in place Attached tools can easily be released
- by pressing the button • Locking function of the lever offers protection
- against unwanted switching • Surface: with protective insulation
- Protective insulation up to 1,000 V
- IEC 60900
- For manual operation









ul. Sarni Stok 73 a, 43-300 Bielsko-Biała, Polska; www.hermestools.eu

Mobil: +420 731 018 782 Mobil: +420 603 530 174




179NXL-8/388 EAN-No. 4000896268801

Assistent with 388 expert tools for commercial vehicles • Tool trolley 179NXL-8 with stainless steel work surface

- 7 flat drawers and 1 high drawer









Screwdriver set 163-619/35 · 4/3+

◆ ◆ ○



Tool assortment 163-618/184 · 4/3+



Tool assortment 163-620/42 · 4/3+



3/4" Socket set 163-406/20 · 3/3 20 3/4" (E) s 19 – 60 mm 163-522X50 soft foam insert



1/2" · 3/4", 24 mm Impact socket set 163-612/40 • 2/3+ 125 1/2 20 3/4 🗘 🔞 🔘 🔘 s 24 mm



Tool assortment 163-621/53 · 3/3+ **8**% ○ **○** ○ **○**







Box-end wrench set - striking face pattern 163-622/3 \cdot 1/3+

Tool assortment 163-623/4 · 1/3+

TORX® box-end wrench set - striking face pattern 163-624/3 \cdot 1/3+ 20 ¾ 🎓 📵





TecDoc® Data supplier



Your HAZET specialist dealer





D-42857 Remscheid, Germany