



HEAVY DEALS

2025-1



HERMES
TOOLS

TecDoc
DATA SUPPLIER

EINFACH VIGOR.

Valid from 01/04/2025 to 28/02/2026 – errors excepted



HEAVY25/EN/XX/0

V8663

EAN 4047728086639

Commercial vehicle ball joint puller for tight installation spaces

- Compact puller for removing ball joints in tight installation spaces, e.g. on **SCANIA** Next Generation trucks


New


Enables quick removal without time-consuming removal of surrounding components!



5


V8664

EAN 4047728086646

Expansion set ball joint puller for 8.5 t cylinder V2873

- Cylinder not included in the set


New


4


V2920

EAN 4047728029209

Ball joint puller · universal

- For removing the ball joint pivots from steering arms on vans, trucks and buses
- Slim construction – for **MERCEDES-BENZ** Sprinter and **FORD** Transit ball joints
- V2873 compressive and tractive hydraulic cylinder 8.5 tonnes, available separately



Cylinder not included in delivery



V2873

Impact function to multiply the pressing force up to 25.5 tonnes of compressive force!

1





V5916-XLEAN 4047728**066471****Ball joint ejector**

- For the hydraulic removal of the ball joint pivots on steering tie rods as well as stabilisers, or steering and brake levers on trucks and buses, with a maximum compressive force of 8.8 tonnes
- Pressing out and pressing in of wheel bolts possible

8.8 t


pressing force



3

**V5912**EAN 4047728**059374****Universal puller for steering arms**

- Adjustable puller with universal application, for loosening almost all spherical joint bearings and steering arms
- Can be used in combination with an 18- or 22-tonne hydraulic cylinder V4551 or V2854
- The wedge-shaped press feet allow optimum access for separating components
- Time saving and risk minimisation through direct application on the vehicle



9



VIGOR No.	Designation	EAN 4047728+
V5912-1	Pressure foot, 2 pieces	059381
V5904-3	Sliding plate	059138
V5904-4	Screw · M14 x 2 – 45 · inside hexagon	059145




V2867N

 EAN 4047728**077859**

Circlip tool

- Removal of internal circlips in wheel bearings
- For passenger cars, vans and trucks
- Sophisticated design covers all working angles and circlip sizes
- Quick changing of spare tips

The circlip tool during application ➤



Ø 2.5 mm

Ø 3.0 mm

Ø 3.5 mm



Spare pins for V2867N

VIGOR No.	Designation		EAN 4047728+
V2992	Pin Ø 2.5 mm	2	029926
V2993	Pin Ø 3.2 mm	2	029933
V2994	Pin Ø 3.5 mm	2	029940




7

V2846

 EAN 4047728**028462**

Pneumatic hydraulic foot pump


- Convenient and direct operation thanks to pneumatic support and highly sensitive foot pedal
- Pressure gauge shows working pressure
- Robust housing protects high-quality built-in components


V2847

 EAN 4047728**028479**

Mechanical hydraulic foot pump

- Stands securely and solidly on its feet
- Robust steel body
- Foot-operated – no pneumatic connection required and thus flexible and mobile in use
- Ideal for mobile use



VIGOR No.	Designation	EAN 4047728+
V3120	2.2 m hydraulic hose 1/4"	031202
V3141	(CEJN) quick coupler connection	031417



V2873

EAN 4047728028738

Tractive and compressive hydraulic cylinder 8.5 tonnes

- Pressing out supporting joints and bushings
- For operation in areas with restricted access
- Thrust rod adjustable

Impact function to multiply the pressing force up to 25.5 tonnes of compressive force!





V2869

EAN 4047728028691

Compressive hydraulic cylinder 14 tonnes

- Pressing out supporting joints and bushings
- Especially for use with the press frames V2885 and V2858N



V4551
EAN 4047728045513

Tractive and compressive hydraulic cylinder 18 tonnes


- Pressing out rusted drive shafts
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- To be used with all passenger car tools and drawbars M10 – M22 with an appropriate reduction



**Extra light:
Only 2.8 kg**



**Impact function to multiply
the pressing force up to
63 tonnes of compressive force!**



10
V2854
EAN 4047728028547

Tractive and compressive hydraulic cylinder 22 tonnes

- Pressing out rusted drive shafts
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- To be used with all passenger car tools and drawbars M10 – M22 with an appropriate reduction



**Impact function to multiply
the pressing force up to
77 tonnes of compressive force!**



10
V2874
EAN 4047728028745

Tractive and compressive hydraulic cylinder 32 tonnes

- Pressing out rusted drive shafts and king pins
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- To be used with all passenger car tools and drawbars M10 – M22 with an appropriate reduction
- The stroke makes it particularly suitable for replacing axle bushings




**Impact function to multiply
the pressing force up to
112 tonnes of compressive force!**


8


V4229

EAN 4047728**042291**
Tractive and compressive hydraulic cylinder 45 tonnes

- Pressing out rusted drive shafts
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body




Impact function to multiply the pressing force up to 157 tonnes of compressive force!



7
V8321

EAN 4047728**083218**
Compressive hydraulic cylinder 70 tonnes

- 70-tonne hydraulic cylinder for commercial vehicle repair workshops
- Mainly for hub removal tools V4554, V4555 and V4500
- To be used in combination with pressing pieces V8323 and V8316
- Weight: 17 kg, stroke: 70 mm
- Automatic piston return function
- In combination with V8667, also suitable for pressing out fixing bolts and king pins



Impact function to multiply the pressing force up to 245 tonnes of compressive force!


2
V8323

EAN 4047728**083232**
Pressing piece 30 mm

- 30 mm pressing adapter for pressing out wheel hubs or steering knuckles, for example
- Only to be used together with cylinder V8321


V8316

EAN 4047728**083164**
Pressing piece 200 mm

- 200 mm pressing adapter for pressing out wheel hubs or steering knuckles, for example
- Only to be used together with the 70-tonne hydraulic cylinder V8321




V4565

 EAN 4047728**045650**

Universal press frame for commercial vehicles 32 tonnes for king pins and fixing bolts

- For the majority of king pins commonly available on the market, including for tapered models
- Unique impact function enables removal with hammer strokes on the cylinder (with mounted impact body) in direction of actuation
- Very effective impact function transmits the vibrations required for successful removal to the material
- Removal of the axle is not necessary
- 32 tonne-version
- Easy to use, also suitable for buses, where access is often restricted
- Also suitable for pressing in and pressing out fixing bolts on agricultural, construction and forestry machinery




10

V4566

 EAN 4047728**045667**

Universal press frame for commercial vehicles 45 tonnes for king pins and fixing bolts

- For the majority of king pins commonly available on the market, including for tapered models
- Unique impact function enables removal with hammer strokes on the cylinder (with mounted impact body) in direction of actuation
- Very effective impact function transmits the vibrations required for successful removal to the material
- Removal of the axle is not necessary
- 45 tonne-version
- Easy to use, also suitable for buses, where access is often restricted
- Also suitable for pressing out and pressing in fixing bolts on agricultural, construction and forestry machinery



12


V8318

EAN 4047728**083188**

Bolt press set

For removal and installation of master pins on chain links

- The mounting plate allows work to be carried out alone
- Mobile and flexible, both in the workshop and in field service
- Internal dimensions of the adapters: Ø 35 mm, Ø 39 mm, Ø 45.4 mm, Ø 48.2 mm
- Only to be used in combination with 45-tonne hydraulic cylinder V4229
- Optimum extension of king pin removal set V4565 and V4566
- Pressure pieces included in the set


24

V8318-1

EAN 4047728**083195**

Expansion set for bolt press set

For removal and installation of master pins on chain links

- The mounting plate allows work to be carried out alone
- Mobile and flexible, both in the workshop and in field service
- Internal dimensions of the adapters: Ø 35 mm, Ø 39 mm, Ø 45.4 mm, Ø 48.2 mm
- Only to be used in combination with 45-tonne hydraulic cylinder V4229
- Optimum extension of king pin removal set V4565 and V4566
- Plates and pressure pieces not included in the set
- Length of the threaded support rods: 383 mm and 557 mm


New

24

V8324


EAN 4047728**083249**

Universal press frame for pressing around fixing bolts, bushing and bearings

- Extra wide press frame for crane trucks, excavator arms or chain links
- Suitable for crane trucks to container side loaders
- To be used with 32-tonne cylinder (V2874) or 45-tonne cylinder (V4229)
- Expandable with pressure sleeve set V5914



Cylinder not included in delivery



4


V8667

EAN 4047728086677

Universal press frame for commercial vehicles 70 tonnes for king pins and fixing bolts

- For the majority of king pins commonly available on the market, including for tapered models
- Unique impact function enables removal with hammer strokes on the cylinder (with mounted impact body) in direction of actuation
- Very effective impact function transmits the vibrations required for successful removal to the material
- Removal of the axle is not necessary
- 70 tonne-version
- Easy to use, also suitable for buses, where access is often restricted
- Also suitable for pressing out and pressing in fixing bolts on agricultural, construction and forestry machinery
- Strut length: 515 mm


New

23


V8666

EAN 4047728086660

Extension set universal press frame for commercial vehicles 70 tonnes for king pins and fixing bolts

- Expansion set for 70-tonne cylinders for the universal press frames for 32-tonne and 45-tonne cylinders (V4565 and V4566)
- Strut length: 515 mm, only to be used together with plates V4556 (2x)


New

Enables the use of the 70-tonne compressive cylinder

21



V4604EAN 4047728**046046****Universal pressure tool set 45 tonnes**

- Quick changing of tapered and cylindrical king pins, drawbar bolts as well as large circlips
- Contents:
 - Removal tools for ball joints, brake adjuster, VBG-drawbar bolts
 - Tools for removing wheel hubs
 - 8.8-tonne and 45-tonne hydraulic cylinder with spindle and impact body
 - Ball joint puller V5916-XL for removing ball joints and replacing wheel bolts



**For the challenges of
king pins, wheel hubs, joints
and circlips - all in one!**



V8721
EAN 4047728087216

Pressure tool set 70 tonnes · universal

- Quick changing of tapered and cylindrical king pins, fixing bolts of hydraulic cylinders and drawbar bolts, as well as large circlips
- Contents:
 - Removal tools for ball joints, brake adjuster, V&G drawbar bolts
 - Tools for pressing out wheel hubs, king pins and fixing bolts
 - 8.8-tonne and 70-tonne hydraulic cylinder with pressure piece and impact body
 - Tool for removing and installing circlips


New

48

V8668
EAN 4047728086684

Expansion set 70 tonnes for BPW and SAF king pins

- Extension set with 70 tonnes release for items V8666 and V8667
- With V4565 and V4566 as the basis, screw V3263 is required four times
- The system enables the pressing in and out of king pins on the trailer using the 70-tonne cylinder, without having to remove the axle in advance



New


610 mm


9


V2858NEAN 4047728**075268****Press frame**

- Suitable for vehicle-specific and universal applications
- Ideal for pressing out and pressing in bolts, bearings and supporting joints
- Pressing force maximum 18 tonnes

**V8669**EAN 4047728**086691****Extension set for bolts on rear hydraulics FENDT & MASSEY FERGUSON**

- Extension kit based on press frame V2858N and the 18-tonne (V4551) or 22-tonne (V2854) hydraulic cylinder for releasing the fixing bolt on the lifting hydraulics at the rear of **FENDT** models of the 500 SCR; 500 S4; 500 Gen3; 700 S4; 700 Gen6 series on which the cone mandrel (743870200110) is installed, as well as on **MASSEY FERGUSON** models of the series: MF 6700S · MF 6S · MF 7700 (S) · MF 7S · MF 8S
- Press frame and hydraulic cylinder not included
- If necessary, the bolt can also be pulled with the traction side of the cylinder in combination with the threaded rod V3220 and the threaded adapter V3219 (both not included in the set) with a maximum of 9 tonnes



**Enables a fast removal
of the fixing bolt
without damage!**

V4635EAN 4047728**046350****Spring bushing set · universal**

- Allows changing of spring bushings without unnecessary disassembly
- Including tool parts for replacing the spring-loaded joint bushing
- For bushings size 44 to 63 mm
- Easy removal, even of rusted bushings, due to impact function



9




V4569

 EAN 4047728**045698**

King pin removal expansion set

- Expansion set for the items V4565 and V4566
- The system allows the pressing in and out of king pins on trailers without removing the axle in advance




9

V4605

 EAN 4047728**046053**

King pin removal expansion set for MERCEDES-BENZ Actros and Atego

- Expansion set for the items V4565 and V4566
- System allows extraction and insertion of king pins to be carried out directly on the vehicle




6

V4606

 EAN 4047728**046060**

Steering knuckle removal expansion set MAN TGA · TGX and TGS

- Expansion set for the items V4565 and V4566
- System allows extraction and insertion of king pins to be carried out directly on the vehicle



5

V5917

 EAN 4047728**059831**

Adjustable tripod mount

- The holder allows you to work at different angles
- Serves as an extension to the V4565 and V4566 press frames
- Adjustable both horizontally and vertically
- Bracket can be adapted to transmission jacks or hydraulic cylinders
- The bracket has inside diameters of 25 mm and 30 mm
- The multiple positions on the flange in combination with the swivelling head maximise access under the vehicle
- Optimised application for the press plate V4556



3

V8315

EAN 4047728**083157**
Dismounting pipe for pressing out the steering knuckle of ZF axles, MERCEDES BENZ and Setra

- The recess for the shock absorber bracket ensures optimum positioning and safe removal of the king pin
- Impressively dimensioned dismounting pipe for use with the 45-tonne cylinder V4229
- Use with press frames V4565 and V4566


V8325

EAN 4047728**083256**
Adapter plate for Volvo steering knuckle bolt

- Adapter specially designed for **Volvo** axles, cone centres the press plate during application
- Only to be used together with press frame V4550


V8314

EAN 4047728**083140**
Pressure sleeve for SCANIA king pins

- Sleeve for pressing out tapered king pins on **SCANIA** vehicles


V2929

EAN 4047728**029292**
Steering knuckle removal extension for Volvo

- Pressure piece is required for pressing out the steering knuckle on **Volvo** axles
- Pressure piece is supported on the carrier to prevent the bearing from being pressed out


V2936

EAN 4047728**029360**
Bushing set · for SAF axle · 150 mm

- Quick, easy removal / installation of the large rubber bushings 150 mm on **SAF** axles
- Recommended for use with 32 tonnes hydraulic cylinder V2874 (not included)



Length of spindle M22 - 250 mm

32t



6


V8317

EAN 4047728**083171**
Extension bushing set

- For replacing bushings on **BPW** and **ROR** axles in combination with our recommended hydraulic cylinder V2874
- Set is also the extension of item V8317 for **SAF**, **JOIST**, **MB** and **ROR** bushings with a diameter of 150 mm

BPW and ROR bushings 119 mm and 139 mm

32t



5



V5066
EAN 4047728050661


Pressure sleeve set

- Adapter and pressure shaft enable application of the press frame V2885 – useful when removing or installing bushings and supporting joints without holes
- Hydraulic cylinder required



Supplied in soft foam insert!

VIGOR No.	Designation	Ø A mm	Ø B mm	Ø C mm	EAN 4047728+
V2947	Pressure sleeve	40.7	42.5	35.2	029476
V2948	Pressure sleeve	43.7	45.5	38.2	029483
V2949	Pressure sleeve	46.7	48.5	41.2	029490
V2950	Pressure sleeve	49.7	51.5	44.2	029506
V2961	Pressure sleeve	52.7	54.5	47.2	029612
V2962	Pressure sleeve	55.7	57.5	50.2	029629
V2963	Pressure sleeve	58.7	60.5	53.2	029636
V2964	Pressure sleeve	61.7	63.5	56.2	029643
V2965	Pressure sleeve	65.7	67.5	60.2	029650
V2966	Pressure sleeve	69.7	71.5	64.2	029667
V2967	Pressure pipe	38.7	44.7	30.5	029674
V2968	Pressure pipe	41.7	44.7	34.0	029681
V2969	Pressure pipe	44.7	44.7	37.2	029698
V2971	Pressure pipe	44.7	55.0	40.2	029711
V2972	Pressure pipe	50.7	55.0	43.2	029728
V2973	Pressure pipe	53.7	55.0	46.2	029735
V2974	Pressure pipe	56.7	55.0	49.2	029742



V5914EAN 4047728**059503****Universal pressure sleeve set with fixing unit**


- The selection of diameters of the pressure pipes and press plates makes this set very versatile for commercial vehicles, either directly on the vehicle or on the workshop press
- The mounting plate included enables the pressure pipes to be fixed to the press block. Work is made easier as fewer parts have to be positioned by hand.
- The set can be supplemented with V5913 to create a complete solution for slotted bushings
- Adapters for cylinders V2874 or V4229 are included in the set
- Hydraulic cylinder required



Supplied in Multibox V4700-XL!

Installation situation of a slotted and tensioned bushing.

V5913 or V5913/6 are required for the installation of slotted bushings.



19

	VIGOR No.	Designation	Ø A mm	Ø B mm	Ø C mm	Length mm	EAN 4047728+
①	V5914-1	Adapter 30 mm	–	–	–	–	059510
②	V5914-2	Adapter 86 mm	–	–	–	–	059527
③	V5914-3	Cylinder adapter	–	–	–	–	059534
④	V5914-4	Fixing plate	–	–	–	–	059541
⑤	V5914-11	Pressure sleeve	64.5	52.5	51.2	32	059558
⑥	V5914-12	Pressure sleeve	69.5	57.5	56.2	32	059565
⑦	V5914-13	Pressure sleeve	74.5	62.5	61.2	32	059572
⑧	V5914-14	Pressure sleeve	79.5	67.5	66.2	32	059589
⑨	V5914-15	Pressure sleeve	84.5	72.5	71.2	32	059596
⑩	V5914-16	Pressure sleeve	89.5	77.5	72.2	32	059602
⑪	V5914-17	Pressure sleeve	93.5	81.5	76.7	32	059619
⑫	V5914-21	Pressure pipe	64.5	62	52	100	059626
⑬	V5914-22	Pressure pipe	69.5	67	57	100	059633
⑭	V5914-23	Pressure pipe	74.5	72	62	100	059640
⑮	V5914-24	Pressure pipe	79.5	77	67	100	059657
⑯	V5914-25	Pressure pipe	84.5	82	72	100	059664
⑰	V5914-26	Pressure pipe	89.5	87	73	100	059671
⑱	V5914-27	Pressure pipe	93.5	91.5	88.5	100	059688
⑲	V5914-28	Pressure pipe	110	107	96	100	059695



V5913
EAN 4047728059398

Basic set for slotted bushings

- Set for universal crimping of slotted bushings
- Slotted silent blocks must be installed in the beam under pretension
- Using a vice or a hydraulic unit in combination with the included clamping device, the bushing is tensioned before installation
- Thanks to the locking pin, no constant pressure needs to be exerted on the clamping device
- Pressure sleeve set V5914 or V5066 is required to press around the bushing
- The set includes shells for bushings with diameters of: 65, 70, 75, 80, 85 and 95 mm
- Recommended for use with 32-tonne hydraulic cylinder V2874 (not included)



Supplied in Multibox
V4700-XL!

VIGOR No.	Designation	EAN 4047728+
V5913-1	Clamping piece 95 mm	059404
V5913-4	Bolts	059435
V5913-65	Adapter Ø 65 mm, 2-piece	059459
V5913-70	Adapter Ø 70 mm, 2-piece	059466
V5913-75	Adapter Ø 75 mm, 2-piece	059473
V5913-80	Adapter Ø 80 mm, 2-piece	059480
V5913-85	Adapter Ø 85 mm, 2-piece	059497


7
V5913/6
EAN 4047728083263

Expansion set for slotted bushings

- To be used in combination with main set V5913
- Set includes shells for slotted bushings with diameters: 50, 56, 58, 60, 63, 68 mm
- Recommended for use with 32-tonne hydraulic cylinder V2874 (not included)



Supplied in Multibox
V4700-XL!

VIGOR No.	Designation	EAN 4047728+
V5913-50	Adapter Ø 50 mm, 2-piece	087070
V5913-56	Adapter Ø 56 mm, 2-piece	087087
V5913-58	Adapter Ø 58 mm, 2-piece	087056
V5913-60	Adapter Ø 60 mm, 2-piece	087063
V5913-63	Adapter Ø 63 mm, 2-piece	087049
V5913-68	Adapter Ø 68 mm, 2-piece	087094

Installation situation of a slotted and tensioned bushing


6

V8320EAN 4047728**083201****Bushing set BPW and ROR**

- Bushing set for replacing the 119 mm and 139 mm rubber bushing on **BPW** and **ROR** axles
- Efficient and safe removal and installation of the silent block
- Recommended for use with 32 tonnes hydraulic cylinder V2874 (not included)



32t



8

**V4555**EAN 4047728**045551****Wheel hub puller set for trucks · buses and trailers 45 tonnes**


- Wheel hubs of trucks with 8 bolts, 275 mm, or 10 bolts, 335 mm
- Removing wheel hubs with compact bearings e.g. on **SAF** axles
- Sturdy construction facilitates the full power of 45 / 70 tonnes together with impact force when removing the wheel hub

45t / 70t



**Article approved
for impact
function!**

**Also suitable
for 70 tonnes!**



VIGOR No.	Designation	EAN 4047728+
V3263	Screw · M22 x 60 mm	032636
V4556	Plate with thread for V3750 · V4554 · V4555	045568
V3222	Pressure foot	032223
V4546	Thrust rod · M30 · length 140 mm · Ø 38 mm	045469
V4545	Thrust rod · M30 · length 30 mm · Ø 38 mm	045452
V4549	Extension · 100 mm · Ø 38 mm for V4555 · V4566	045490
V4547	Extension · 50 mm · Ø 38 mm for V4555 · V4566	045476
V4548	Extension · 70 mm · Ø 38 mm for V4555 · V4566	045483

12



V4500

EAN 4047728045001

Wheel hub puller commercial vehicle · 45 tonnes

- Removal of rusted bearings with outside wheel hubs from straight shafts
- For: **Volvo** FL · TGS · TGX · **MERCEDES-BENZ** Atego · Actros · **RENAULT** Kerax · Magnum · Midlum · Premium
- Can also be used for vehicles with identical construction
- 45- / 70-tonne version




**Can also be used
with 70 tonnes!**

**Article approved for
impact function !**



M30 thread



3

V3750

EAN 4047728037501

Wheel hub extractor for low-height trailers

- Removal of 225 mm wheel hub with 10 screws
- Extractor enables loosening of hubs with bearing unit on straight shafts
- Recommended for use with 32 tonnes hydraulic cylinder V2874 (not included)
- Sturdy construction enables pressure up to 45 / 70 tonnes and hammer stroke in direction of pressure



**Article approved
for impact
function !**

**Can also be used
with 70 tonnes!**




15

V8322EAN 4047728**083225****Wheel and rim puller for trucks**

- Rim puller for efficient and safe removal of stuck wheels/rims
- Quick and effortless removal in just a few minutes
- Three receiving adapters for pressure sleeves in a set for truck, bus and trailer rims: 22.5", 19.5", 17.5"
- Application with an impact wrench, alternating pressure on screw connections
- Four rim hooks fit into most rim ventilation holes
- Saves time and effort, an essential investment for workshops that encounter stuck wheels
- Traditional methods are tedious, dangerous and reduce workshop productivity

The rim is loosened in just a few minutes


1. Install the bolt ring
2. Install the mounting rod
3. Install the hook and chain
4. Use an impact wrench to pull the rim off the hub



17

**V3678**EAN 4047728**036788****Brake disc removal (floating) · Volvo · RENAULT · DAF**

- Removal of floating brake discs
- Removal of the brake disc by alternately pressing the cylinders
- Two special cylinders and two-way control valves for alternate pressing
- Brake disc removal in just a few minutes



VIGOR No.	Designation	EAN 4047728+
V3678-1	Clutch set extension · 4-piece	087124

V5907EAN 4047728**059206****Spare cylinder 14 tonnes**

V4972

EAN 4047728087179

Hydraulic lifting tool for trucks

- Lifting aid with high loading capacity (450 kg), which makes lifting heavy loads superfluous. The design offers maximum access and flexibility for ergonomically correct work on trucks, trailers and buses.
- Lifting heavy loads in combination with an incorrect working posture poses a major risk to the working environment and the health of the mechanic. The flexible lifting arm for the press frame provides excellent access when replacing the king pin on the steering knuckle.
- Wheel hub removal is effortless, the powerful hydraulic cylinders (45-tonne V4229 and 70-tonne V8321) are fixed in the supplied tool holder. Wheel hubs with brake discs or brake drums, wheel hubs with dual tyres in combination with brake drums are raised and lowered onto the vehicle without any manual force.
- Thanks to the four large swivel castors, the lifting aid is easy to move and manoeuvre, even with a maximum load of 450 kg. If required, the front wheels can be locked in the straight-ahead position.
- When replacing the king pin etc., the hydraulic pump supplied can be easily removed from the lift truck so that it can be used on the ground. Both practical handles on the rear wheels are very helpful during installation of the hub onto the wheel axle.
- CE-marked product for maximum safety
- ISO 45001 Occupational health and safety management standard in the EU
- The lifting platform can be supplemented with accessories such as a universal device for removing brake callipers and a holder for the press frame when replacing bushes
- Height-adjustable by means of hydraulics.
Also variable in the basic position via rectangular perforation.



6




Available from May 2025!



New



Press cylinder holding device



V7275
EAN 4047728072755

Multibox · starter set · wheel bearing of van front axle

- More mobility in the fields of trade, industry and service
- Considerable time savings thanks to usability directly on the vehicle, estimated time per side is approx. 30-40 minutes
- Replacement of the front axle wheel bearing in the following models:
 - **CITROËN** Jumper
 - **FIAT** Ducato
 - **PEUGEOT** Boxer since 2007
 - **RENAULT** Master
 - **NISSAN** Interstar
 - **OPEL** Movano since 2010
 - **FORD** Transit since 2000
- The 32 tonne cylinder V2874 is required to use the tool set
- Can optionally be extended for rear axle wheel bearings for diverse models of transport vehicles with V7291
- Cylinder not included in delivery


**SUV
Van**


» For components,
see VIGOR
main catalogue
page 395


18

V7251
EAN 4047728072540

Multibox wheel bearing set IVECO Daily

- More mobility in the fields of trade, industry and service
- Replacement of the front axle wheel bearings in the installed condition on **IVECO** Daily from model year 2014 →
- To be used with 32-tonne hydraulic cylinder V2874
- Alternative use after removal with the aid of a workshop press
- Cylinder not included in delivery


**SUV
Van**


» For components,
see VIGOR
main catalogue
page 394


11


V7133
EAN 4047728071338

Compact wheel bearing removal / installation set

- Including multibox
- Operating all compact wheel bearings from Smart to the Sprinter
- Utilised assembly unit V4491 ensures professional installation of the second generation compact wheel bearing
- Contents: Special unit for installing the closed wheel bearing and a universal set for all other compact wheel bearings diameters
- Cost and time savings by eliminating the need to install a new steering knuckle, the subsequent axle alignment and the associated additional work
- Including two V4700-L multiboxes
- Special set for installing the wheel bearing closed at the wheel hub for the following vehicles, among others:
MERCEDES-BENZ V-Class model year 2014 → · Viano model year 2003 → · Vito van model year 2014 → · Sprinter model year 2008 →
- **VOLKSWAGEN** Crafter model year. 2011 →
- Cylinder not included in delivery



» For components,
see VIGOR
main catalogue
page 342

2x



35


V7154-4
EAN 4047728071765

Brake disc removal kit

- Separates severely rusted brake discs and those that are stuck to the wheel hubs
- Heavy hammering on the brake disc can cause damage to the wheel bearing
- Transmission of even pressure across the removal tool feet onto the brake disc. The hydraulic cylinder is supported by an adapter piece on the drive shaft screw connection
- Significantly minimises the risk of damage with an even transmission of force to the brake disc from the four feet
- Recommendation: use of a hydraulic cylinder, e.g. V4551 or V2854
- Alternative application with V4699
- Span width: 260 – 330 mm
- Maximum loading capacity: 22 tonnes
- Cylinder not included in delivery



» For components,
see VIGOR
main catalogue
page 345



21



V7276-2

 EAN 4047728**072908**

Mobile work bench with van / SUV specialty tool assortment and hydraulic foot pump


V7265


Ball joint ejector, hydraulic 8.8 t

- For the hydraulic removal of the ball joint pivots on steering tie rods as well as stabilisers, or on steering and brake levers for trucks and buses, with a maximum compressive force of 8.8 t
- Height adjustment 81 and 113 mm as well as adjustable diameter to 42 and 56 mm
- The design optimises access to hard-to-reach areas



Tractive and compressive hydraulic cylinder 32 t

- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- With the correct adapter, drawbars of M 10 to M 22 can be used


V5058

Tractive and compressive hydraulic cylinder 22 t

- With automatic piston return
 - Pressure of the hydraulic cylinder may be combined with impact force when using an impact body.
- Application: e.g. for removing rusted drive shafts

Including: V2846 Hydraulic pump · pneumatic

- Design including manometer
- For all hydraulic cylinders
- Working pressure: 700 bar
- Hose length: 2.2 m
- Oil tank: 1.3 l
- Non-drip quick coupling




700 bar



1.3 l



2.2 m



Can also be used to store the pump.


V7261


Circlip tool

- Facilitates the removal of frequently rusted circlips on the inside of wheel bearings
- Maximum force and fast removal due to adjusting screw with recesses for a 6.3 = 1/4" ratchet
- Clamping range: 5 – 95 mm
- Includes 2 tips each: Ø 2.5 mm / Ø 3.0 mm / Ø 3.5 mm



Drive shaft press-out device · 6- and 8-hole

- For removing rusted and glued drive shafts directly on the vehicle
- For bolt circle (6 hole) 114–140 mm, (8 hole) 165 to 180 mm
- Removal of drive shaft with 22 t hydraulic cylinder (installation of the impact body enables use of additional force by using a hammer)

Wheel bearing unit, screwed, removal tool set · universal

- For removing screwed wheel bearings with 3-4 bolts
- SUV / VAN wheel hubs with 6 and 8 stud bolts to 180 mm diameter can be removed via the adjustable crossbar
- For among others: **DODGE · CHEVROLET/GMC · FORD** Ranger model year 2011 →

Scraper

- Removing rust from the outer edge of the brake discs as well as from the brake calliper lining
- For cleaning the contact surface of the counter plate on among others **VOLKSWAGEN T5 / T6**


V7263

Expansion set for wheel bearings on IVECO Daily

- The front wheel bearing can be pressed out using the 32 t hydraulic cylinder **V2874** while installed
- Alternatively, the set can also be used with the workshop press when removed





V7270



Expansion set for wheel bearing of van rear axle

- Extension kit for changing rear axle wheel bearings on the following vehicles among others: **CITROËN** Jumper, **FIAT** Ducato, **PEUGEOT** Boxer, **FORD** Transit
- Removal of the drive shaft possible using the 5-hole drive shaft tool (bolt circle 119 - 172 mm)
- Items **V2881** and **V2882** are required for individually replacing rear axle wheel bearings. These are included in the starter set for van front axle wheel bearings
- The 32 t hydraulic cylinder **V2874** is required for use



V7273



Starter set wheel bearing, van front axle

- Allows the wheel bearings to be changed directly on the vehicle with minimum effort using the 32 t hydraulic cylinder **V2874**
- Replacement of the front axle wheel bearing on the following models:
CITROËN Jumper
FIAT Ducato
PEUGEOT Boxer from 2007
RENAULT Master
NISSAN Interstar
OPEL Movano from 2010
FORD Transit from 2000



UPDATE

V7201N



Installation



Removal



Universal compact wheel bearing removal/installation tool set

- For removing and installing compact wheel bearings with or without circlip
- Adjustability enables use on all types of currently available and future compact wheel bearings



V7267

Wheel hub puller

- Removal of screwed wheel bearing units with closed wheel hub. The drive shaft does not have to be removed beforehand anymore
- To be used together with wheel bearing / hub tool **V3731** - **V3732** as well as hydraulic cylinder 16-22 t
- Bolt circle 4 and 5-hole: 92 - 131 mm
- Note: Do not load tool with more than 18 t
- For models with closed wheel hub, among others:
OPEL Insignia model year 2010 →
CITROËN C1 model year 2006 → · Jumpy model year 2016 → · SpaceTourer model year 2016 →
PEUGEOT 108 model year 2015 → · Expert model year 2016 → · Traveller ·
TOYOTA Aygo model year 2006 → · ProAce (Verso) and other models



Wheel hub/wheel bearing puller for 6 and 8 bolts

- Removing screwed wheel bearings and hub units directly on the vehicle
- Only in conjunction with **V5906**
- No need to remove the drive shaft
- The included M 22 threaded rods connect the tool to one of our hydraulic cylinders
- For bolt circle (6 hole) 111.5 - 142.5 mm, (8 hole) 162.5 - 182.5 mm
- Among others for **MERCEDES-BENZ** Sprinter · X-Class, **NISSAN** Pathfinder, **IVECO** Daily, **VOLKSWAGEN** Crafter, **FORD** F-150 · Ranger



V7133N

Wheel bearing expansion set for Sprinter / Crafter

- Recommendation: use of a conventional tool set is not possible as a closed wheel bearing is fitted. Drive with a spindle system is not possible
- Special set for installing the wheel bearing closed at the wheel hub for the following vehicles, among others: **MERCEDES-BENZ** V-Class model year 2014 → · Viano model year 2003 → · Vito box model year 2014 → · Sprinter model year 2008 →
- **VOLKSWAGEN** Crafter model year. 2011 →
- Cost and time savings by eliminating the need to install a new steering knuckle, the subsequent axle alignment and the associated additional work
- Prerequisite: Assembly unit for compact wheel bearing **V4491** as well as drive unit, e.g. hydraulic cylinder **V4551** or **V2854**

PIPE WRENCHES

- Robust cast iron pliers body enables high power transmission
- Quick canting and release on the workpiece due to internal spring
- Coarse jaw serration for optimum grip

HEAVY DUTY

Continuously adjustable



New



Our four pipe wrenches –
your team with a grip
on every problem



VIGOR No.	Length mm	Weight kg	EAN 4047728+
V5639-6	130	0.23	086134
V5639-8	170	0.39	086127
V5639	350	1.3	075589
V5639-24	620	3.2	081719

V6500-190

EAN 4047728084208

Heavy-duty diagonal cutter

- High-performance power side cutter for precise and effortless cutting
- Robust construction and sharp cutting blades for clean and precise cuts
- Ergonomically shaped handles for maximum comfort and control during use



V6504-125

EAN 4047728082617

Universal pliers with pushbutton · 125 mm

- Adjustment of the jaw opening at the touch of a button
- Locking of the hinge pin prevents unintentional adjustment
- Jaw opening: up to 44 mm
- Capacity for nuts, size 27 mm
- Capacity for pipes Ø 29 mm / Ø 1"
- Adjustment positions: 15
- Weight: 89 g



V6504-250

EAN 4047728077750

Universal pliers with pushbutton · 250 mm

- Adjustment of the jaw opening at the touch of a button
- Locking of the hinge pin prevents unintentional adjustment
- Jaw opening: up to 65 mm
- Capacity for nuts, size 46 mm
- Capacity for pipes Ø 50 mm · Ø 2"
- Adjustment positions: 23



V5488EAN 4047728**054881****Multifunctional drain pan · 50 l**


- Alkaline-resistant and acid-resistant
- Volume: 50 l
- Internal dimensions (W x D x H): 800 x 520 x 100 mm
- From TÜV-certified production in accordance with DIN ISO 16901

**V2234**EAN 4047728**022347****5 kg rubber hammer**

- Loosening rusted rims during a wheel change
- Extra-heavy design for commercial, agricultural and industrial vehicles
- Non-rebound due to steel-ball filling in hammer head (hammer does not rebound)
- Plastic handle
- Dimensions / length: 900 mm
- Hammer head weight: 5 kg

**NITRILE GLOVES****Protects hands from oil, grease, chemicals and dirt**

- Surface structure provides good adhesion, even in oily working conditions
- Safety colour orange for better visibility in dark work spaces
- Comfortable, tear-resistant glove with good dexterity
- Touchscreen compatible
- Material: Nitrile
- Latex- and powder-free



VIGOR No.		Size	EAN 4047728+	
V6436-M	100 pcs./carton	M	080118	
V6436-L	100 pcs./carton	L	077712	
V6436-XL	90 pcs./carton	XL	077729	
V6436-XXL	90 pcs./carton	XXL	077736	

V4414EAN 4047728**044141****Oil filter tensioner adjuster · 80 – 115 mm · universal**

- Mechanical locking of the oil filter wrench simplifies subsequent attachment of the reversible ratchet to the oil filter wrench
- The oil filter tensioner adjuster always remains under tension when the reversible ratchet is moved backwards
- Continuously adjustable
- Use with wrench size 21 mm or $\frac{1}{2}$ " reversible ratchet
- Optimal hold when loosening the oil filter thanks to left-toothed jaws
- For oil filters in areas with restricted access
- Clockwise/anti-clockwise application enables operation of the screw connection
- Drive: 22 mm outside hexagon, $\frac{1}{2}$ " (12.5 mm) square
- Diameter (min.-max.): 80 – 115 mm

**V4415**EAN 4047728**062114****Oil filter tensioner adjuster · 115 – 140 mm · universal**

- Mechanical locking of the oil filter wrench simplifies subsequent attachment of the reversible ratchet to the oil filter wrench
- The oil filter tensioner adjuster always remains under tension when the reversible ratchet is moved backwards
- Continuously adjustable
- Use with wrench size 21 mm or $\frac{1}{2}$ " reversible ratchet
- Optimal hold when loosening the oil filter thanks to left-toothed jaws
- For oil filters in areas with restricted access
- Clockwise/anti-clockwise application enables operation of the screw connection
- Drive: 24 mm outside hexagon, $\frac{1}{2}$ " (12.5 mm) square
- Diameter (min-max): 115 - 140



V2461N

EAN 4047728056472

Socket set

- Drive: solid hexagon 6.3 (1/4 inch), solid hexagon 8 (5/16 inch), hollow square 6.3 mm (1/4 inch), hollow square 10 mm (3/8 inch), hollow square 12.5 mm (1/2 inch)
- Output: E profile, outside hexagon profile, internal wedge profile Ribe-CV, T profile, internal serration profile XZN, inside hexagon profile, Phillips-Recess profile PH, Pozidriv profile PZ, slotted profile, TH profile
- Sizes: · 0.8 x 4 – 1.2 x 7 · 1.3 – 32 · E4 – E22 · PH0 – PH2 · PZ0 – PZ2 · T9 – T30
- For manual operation



172



V2318N

EAN 4047728059299

3/4" Socket set

- Drive: square 20 mm (3/4 inch)
- Output: outside hexagon profile
- Sizes: 19 – 50
- Number of teeth: 24 (operating angle 15°)
- For manual operation



20 3/4"



21



V5461

EAN 4047728080323

Socket set

- For manual operation



12-point design



» For components see catalogue page 168



133



V5034/3EAN 4047728**086318****Impact extension set**

- Material: Cr-Mo
- For impact operation
- Ideal for hard-to-reach places

20 3/4"

New

VIGOR No.	Designation	Length mm	EAN 4047728+
V5034-100	Impact extension	100	086349
V5034-200	Impact extension	200	086332
V5034-400	Impact extension	400	086325

3

**V7212**EAN 4047728**072120****Inside hexagon impact screwdriver socket set**

- Common screw connections for VAG vehicles, e.g. brake carriers, central drive shafts, shock absorbers or screwed wheel bearing units
- Drive: 3/4 inch (20 mm) square
- Output: inside serration profile XZN, inside hexagon profile
- Surface: burnished, oiled
- For impact operation

**V5024**EAN 4047728**050241****Impact socket set**

- Extra thin-walled sockets for drive shaft screw connections in the wheel hub
- Adjusted to given spaces in the wheel hub
- Among others for:
 - Size 24: **VW** Touran model year 2006 →
 - Size 30: **VW** Passat C, Golf 4, Polo, New Beetle · **AUDI** TT · **ŠKODA** Octavia, Superb, Fabia
 - Size 32: **VW** Touareg model year 2003 →
 - Size 36: **BMW** 3-series · 5-series · 7-series · **SEAT** Ibiza · **VW** Polo, Golf Plus · **OPEL** Corsa D · Adam · Mokka · **CHEVROLET** Trax model year → 2013 · **FIAT** 500 · Grande Punto · Punto Evo model year → 2005 · **FORD** Ka · **MERCEDES-BENZ** S-Class · **JAGUAR** XJ40 · XJ181
- Drive: 3/4 inch (20 mm) square
- Output: outside 12-point profile
- For impact operation



V4970

 EAN 4047728**086219**

Telescopic ratchet set

- 180° swivel head with locking mechanism
- Quick-release press-button
- For manual operation

S

6.3	1/4"	10	3/8"	12.5	1/2"	20	3/4"
6.3	1/4"	10	3/8"	12.5	1/2"	20	3/4"


New


17


12.5 1/2"



10 3/8"



6.3 1/4"




**Including extension
75 and 250 mm!**

V4970-L

 EAN 4047728**086110**

Telescopic ratchet insert S · empty

New

V5010/12

 EAN 4047728**086981**

Screwdriver with impact cap · including square

- 2-component handle
- Screwdriver with impact cap
- Square in the impact cap
- Hexagon at the blade

+	-	6.3	1/4"
---	---	-----	------

New



VIGOR No.	Designation	EAN 4047728+
V1208	Screwdriver for slotted screws 5.5 x 38	012089
V5010-SL3.5	Screwdriver for slotted screws: 3.5 x 75	086561
V5010-SL5	Screwdriver for slotted screws 5 x 100	086578
V5010-SL6	Screwdriver for slotted screws 6 x 125	086585
V5010-SL8	Screwdriver for slotted screws 8 x 150	086592
V5010-SL10	Screwdriver for slotted screws 10 x 200	086608
V1209	Phillips-Recess screwdriver PH2	012096
V5010-PH0	Phillips-Recess screwdriver PH0	086516
V5010-PH1	Phillips-Recess screwdriver PH1	086523
V5010-PH2	Phillips-Recess screwdriver PH2	086530
V5010-PH3	Phillips-Recess screwdriver PH3	086547
V5010-PH4	Phillips-Recess screwdriver PH4	086554



12

V6050EAN 4047728**086141****One-hand multifunctional wrench**

- Chrome-vanadium
- Multifunctional wrench with ratchet function
- Automatic adjustment to the screw size
- Wrench sizes: 8 - 17 · 14 - 32
- Self-clamping

**New****V1001/2**EAN 4047728**086752****Impact rod set**

- Diameter 25 mm and 16 mm
- Exchangeable nylon caps
- Impact rod 25 mm with steel ball filling (non-rebound)
- Extension for hammer
- Precise and secure impact possible

**New**

VIGOR No.	Designation	Ø mm	EAN 4047728+
V1001-16	Impact rod	16	086707
V1002-16	Nylon spare cap	16	086738
V1001-25	Impact rod	25	086721
V1002-25	Nylon spare cap	25	086745

2**MACHINIST'S HAMMER**

- Hickory wood handle
- High-quality hammer with rubber impact protection
- Sturdy design for long-lasting performance and reliability



VIGOR No.	Length mm	Weight g	EAN 4047728+
V2662-300	300	300	084444
V2662-500	320	500	084451
V2662-800	350	800	084437
V2662-1000	360	1000	084420

V2663-1500EAN 4047728**084383****Club hammer**

- Hickory wood handle
- High-quality hammer with rubber impact protection



V7740/6

EAN 4047728084499

Combination wrench set XXL

- Chrome-vanadium
- DIN 3113
- Surface: chrome-plated, polished



34 · 36 · 38 · 41 · 46 · 50 mm



6


V6640

EAN 4047728085588

Combination wrench set XXL in soft foam insert

- For contents see V7740/6

L



6


V7031

EAN 4047728082624

Ratcheting box-end wrench set · extra long

- At least 60 % longer than standard ratchet wrenches – for greater power transmission
- Slim design
- Tool roll
- Surface: chrome-plated, polished
- 72 teeth
- 5° operating angle

10 · 11 · 12 · 13 · 14 · 15 ·
16 · 17 · 18 · 19 mm



10


V2338

EAN 4047728023382

Kneeling mat


- Comfortable working in the workshop, industry, garden or household
- High-quality foam
- Knee-protecting
- Heat insulating
- Water and oil repellent
- With carrying handle
- Dimensions: 475 mm x 235 mm x 26 mm



V2338-XL

EAN 4047728071444


Mechanic's mat

- Comfortable working on the floor in the workshop, industry, garden or household
- Large lying surface
- High-quality foam
- Low-impact
- Pliant and heat-retaining foam
- With two handles
- Dimensions: 980 mm x 480 mm x 27 mm



V5671NEAN 4047728**076715****MINI GIANT****1/2" Impact wrench · mini****12^S 1/2"****1/2"**
1200 Nm

Ø mm	Nm	max. Nm	max. Nm	rpm	kg	l/min.	bar	m/s ²
12,91 (16) 7,2	600	850	1200	10000	1.28	141.5	6.3	6.81

**V6899N**EAN 4047728**076944****GIGA GIANT****3/4" Impact wrench***The most
powerful
in its
class!***20 3/4"****3/4"**
2300 Nm

Ø mm	Nm	max. Nm	max. Nm	rpm	kg	l/min.	bar	m/s ²
16,41 (16) 7,2	1400	2000	2300	5500	3.60	254.8	6.3	5.75

**V5505N**EAN 4047728**080484****Impact universal joint set**



- Working in areas with restricted access, and for getting around obstructive edges

6.3 1/4" 10 3/8" 12^S 1/2"**6.3 1/4" 10 3/8" 12^S 1/2"****3**

VIGOR No.			EAN 4047728+
V5505N-1/4	6.3 1/4"	6.3 1/4"	083324
V5505N-3/8	10 3/8"	10 3/8"	083317
V5505N-1/2	12^S 1/2"	12^S 1/2"	083300

AIR BLOW GUNS

- Fast removal and cleaning of chips and other foreign objects
- Long-life aluminium housing
- Suspension device incorporated



VIGOR No.	Design	EAN 4047728+
V7135	Short	071352
V7135-150	Long · tip 150 mm	071369

V7501-39

EAN 4047728082037

Video borescope with Ø 3.9 mm probe


Analysis and documentation of damage patterns in difficult to access spaces!

- Probe: Ø 3.9 mm
- Probe length: 1000 mm
- Camera resolution: 1280 x 720 (corresponds to HD quality)
- Camera viewing angle: 80°
- 6 dimmable LEDs
- Depth of field: 20 – 80 mm
- 5" display, swivelling
- Display resolution: 1280 x 720 pixels
- 6 Ah, 3.7 V Li-ion rechargeable battery
- 2A/5V power supply unit, USB charging cable and 32 GB TF memory card included in delivery

Screen can be moved freely in all directions



Swivels 180° on both sides



Your tool deserves a better home!

Find the perfect empty tool trolley for your needs.
Individual just like you! You decide. Come and snap up the perfect model for you!

Series M – Small but mighty



Total loading capacity

V5489

EAN 4047728054898

Price with foam mat



L: 681 mm
W: 460 mm
H: 1016 mm



Series L – The all-rounders



Total loading capacity

V1901

EAN 4047728019019

Price with plastic worktop



L: 733 mm
W: 481 mm
H: 1002 mm



V1901-X

EAN 4047728083072

Price with stainless steel worktop

25% more drawer capacity compared to Series M

Series XL – Bigger is better



Total loading capacity

V4481

EAN 4047728044813

Price with plastic worktop



L: 949 mm
W: 523 mm
H: 1017 mm



V4481-X

EAN 4047728060721

Price with stainless steel worktop

33% more drawer capacity compared to Series M

Series XD – The space saving boss



Total loading capacity

V4481-XD

V4481-XD

EAN 4047728066488

Price with stainless steel worktop



L: 986 mm
W: 695 mm
H: 1017 mm



53% more drawer volume compared to Series XL

Series XXL – For everything big



Total loading capacity

V4481-XXL

V4481-XXL

EAN 4047728080491


Price with stainless steel worktop



L: 1615 mm
W: 686 mm
H: 1035 mm



Monster drawer





With stainless steel worktop

**Tool trolley
available with
assortment
1 or 2!**

Drawers:

- 7x flat
- 1x high

L x W x H
723 x 459 x 1002 mm



With plastic worktop

**Tool trolley
available with
assortment 2!**

Drawers:

- 6x flat
- 2x high


L x W x H
723 x 459 x 1002 mm

ASSORTMENT 1 Including tool trolley with stainless steel worktop


V4188



V4753



V6724N



V5006

V5017

V4995



V5068

V4991

V5070



V5004

V5072

V5633N



V6811



442
tools including
tool trolley


VIGOR No.		Designation	kg	EAN 4047728+
V1901-X/442	442	Tool trolley with stainless steel worktop and assortment 1	131	084338

ASSORTMENT 2 Including tool trolley with stainless steel or plastic worktop

V4188



V4753



V6724N



376
tools including
tool trolley

V5068

V5070

V5006

V5633N

V5603

V7324



VIGOR No.		Designation	kg	EAN 4047728+
V1901-X/376	376	Tool trolley with stainless steel worktop and assortment 2	119	084192
V1901/376	376	Tool trolley with plastic worktop and assortment 2	100	080293


V4813/NKW

EAN 4047728085687

Work bench advantages

- Robust wooden worktop
- Vice V6150N can be screwed on (not included in delivery)
- Door allows large tools to be stowed away
- Including 7 inserts

+7
inserts!


 L x W x H
1091 x 481 x 1018 mm


Our tip!
Vice
V6150N




V1901-X/NKW

EAN 4047728085601

Tool trolley advantages

- Compact design
- Saves a lot of space in the workshop
- Stainless steel worktop: resistant to dirt
- Including 7 inserts

+7
inserts!


 L x W x H
723 x 459 x 1002 mm


Our tip!
Laptop table
V6221



Both tool trolleys come with 7 inserts!

L

2
K


Advantages of inserts

- 3/4" socket set for heavy-duty use (V5109)
- XXL Combination wrench as problem solver (V6640)
- Fine-tooth solid steel ratchets for use on commercial vehicles



19 · 21 · 22 · 23 · 24 · 26 · 27 · 28 · 30
32 · 34 · 36 · 38 · 41 · 46 · 50 mm

34 · 36 · 38 · 41 · 46 · 50 mm






With stainless steel worktop

**Tool trolley
available with
assortment
1, 2 or 3!**








With plastic worktop

**Tool trolley
available with
assortment
1 or 3!**



Edge protection

ASSORTMENT 1 Including tool trolley with stainless steel or plastic worktop



499

tools including
tool trolley

VIGOR No.	XX	Designation	kg	EAN 4047728+
V4481-X/499	499	Tool trolley with stainless steel worktop and assortment 1	150	062367
V5434	499	Tool trolley with plastic worktop and assortment 1	141	054348

ASSORTMENT 2 Including tool trolley with stainless steel worktop

V4586



V6650N



V7015N



V6015



V5170



Including accessories

466

tools including
tool trolley


VIGOR No.		Designation	kg	EAN 4047728+
V4481-X/466	466	Tool trolley with stainless steel worktop and assortment 2	140	074674

ASSORTMENT 3 Including tool trolley with stainless steel or plastic worktop

V4586



V6650N



V5170



V5638N



375

tools including
tool trolley

VIGOR No.		Designation	kg	EAN 4047728+
V4481-X/375	375	Tool trolley with stainless steel worktop and assortment 3	127	062350
V4542	375	Tool trolley with plastic worktop and assortment 3	117	045421






The space saver!

» With stainless steel worktop

» Drawer slide out 100 %

EXTRA DEEP!



775
tools including
tool trolley

VIGOR No.		Designation	kg	EAN 4047728+
V4481-XD/775	775	Tool trolley with stainless steel worktop and assortment	210	068529

LD

XD

XXD

VIGOR
 SERIES **XXL**

In a class of its own!

» With stainless steel worktop

» Drawer slide out 100 %



EXTRA DEEP + EXTRA WIDE!

 L x W x H
 1625 x 695 x 1017 mm


V6830

V6831

V6807N

V6808N

Discover a new dimension of reality! »



V6813


V6814

V6809

V6810

V6565

V6811



Including socket strip with 2x USB and 2x USB-C as well as 2-metre H07 cable with safety plug



V6817

V6818

929 +

tools including tool trolley



Including can holder V2393-XXD



VIGOR No.



Designation



EAN 4047728+

V4481-XXL/929

929

Tool trolley with stainless steel worktop and assortment


296

082303

FOR SCREWING


V6221, EAN 4047728062213

Laptop table




V6393, EAN 4047728069519

Document holder




V6395, EAN 4047728070522

Waste bin




V6398, EAN 4047728071314

Laptop holder · rotatable and pivotable



V6393-S, EAN 4047728069205


Document holder · small



MAKE YOUR TOOL UNIQUE!


V6396, EAN 4047728069601

Screwdriver holder




V2397, EAN 4047728023979

Holder for paper reel




V6394, EAN 4047728069595

Impact wrench holder




V6397, EAN 4047728069793

Holder for paper reel · pivotable





V2393, EAN 4047728023931

Can holder




TO HOOK ONTO PERFORATED TOOL PANEL PLATE 9 x 9 mm

Perforated tool panel plate for tool trolleys



V6399




V6399-XD

VIGOR No.	Designation	EAN 4047728+
V6399	For Series M, L and XL	085533
V6399-XD	For Series XD and XXL	085540

V6000-059, EAN 4047728085557


Cordless tool holder




TROLLEY

**V6000-055**, EAN 4047728077118

Torque wrench holder

**V6000-055XL**, EAN 4047728077125


Torque wrench holder · large




Tool hook set

V2517


EAN 4047728025171

**V2518**

EAN 4047728025188

**V2519**


EAN 4047728025195

**V2520**


EAN 4047728025201

**V6000-060**, EAN 4047728085526

Glove box holder

**V6150N**, EAN 4047728084734

Vice



Whether on your tablet, laptop or computer. Start configuring now!




www.vigor-equipment.com/konfigurator

Click here for the
KonVIGORator



New functions

- **Augmented Reality***: Besides the new 3D function, our KonVIGORator now has the option of "placing" your planned wall unit directly where you want it! All you need is a mobile phone or a tablet with a camera. You can either configure directly on your mobile device or relaxed on your computer and then scan the QR code.
- **Availability display**: Now you can already see whether an item is available when configuring it



*Latest system software required

Our 700 mm depth now offers you even more storage space!

In the current system, the 500 mm cabinets are extended to 700 mm with our extension frames and thus offer you even more working space.

Our new lower cabinets from the XD family now offer you even more lower cabinet space – namely the full 700 mm! More space for tools, small parts and much more!

We start with our three most popular lower cabinets. If you like the new system as much as we do, more cabinets will follow – so stay tuned!


PS.: Of course, you can also find the new lower cabinets in the KonVIGORator!




OUR STARTER KIT

Storage system


- 3-module combination in wide design
- Available with wooden or stainless steel worktop
- Including side veneer



Also available with wooden worktop!



Feet adjustable
in height to 50 mm




VIGOR No.	Designation	EAN 4047728+
V6000-3P1XL	Storage system combination · starter kit · wooden	073318
V6000-3P1XL-X	Storage system combination · starter kit · stainless steel	073271

OUR COMPLETE KIT

Storage system


- 3-module combination in wide design with perforated panel structure and wall cabinets
- Available with wooden or stainless steel worktop
- Including side veneer




Feet adjustable
in height to 50 mm



**Configure your
storage system
now!**



Also available with wooden worktop!



VIGOR No.	Designation	EAN 4047728+
V6000-3P2XL	Storage system combination · complete kit · wooden	073301
V6000-3P2XL-X	Storage system combination · complete kit · stainless steel	073295



Powerful variant! 3.5 kW

V4891-3.5

EAN 4047728072779

Induction heater · 3.5 kW

- Modern and efficient heating – prevents damage to surrounding components
- Targeted heating within seconds
- Cooling fluid and focus coil included in delivery
- Water cooling up to the coil head
- Avoidance of overheating thanks to integrated ventilator
- Extensive accessories for various application fields
- Highest possible capacity in compact design •
- Output power can be precisely adjusted for the application field – from 10 – 100%
- Operating information via LED display on the handle



3.5
kW



Coils optionally available,
not included in delivery.

2

